

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 080597

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

PO Box 990, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1190'S, 1650'W

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gartner

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 26, T-30-N, R-8-W
NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5911'GL

12. COUNTY OR PARISH

San Juan

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☒

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☐
☐

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In order to increase production, it is planned to workover and restimulate this well in the following manner:

Pull tubing; if tubing is stuck, cut off approximately 100' below the 7" casing shoe, set a drillable cement retainer near the bottom of the 7" casing shoe, squeeze the open hole with 150 sks. cement.

Pressure test the 7" casing to 1000 psi.

Isolate and squeeze any leaks. If leaks are squeezed near the base of the Ojo Alamo, no additional block squeeze of the 7" annulus is planned.

If there are no leaks near the base of the Ojo Alamo, perforate squeeze holes at the base of the Ojo Alamo and block squeeze with 125 sks. cement.

Clean out and sidetrack a new hole to approximately 5360'. Run a full string of 4 1/2" production casing. Cement with sufficient cement to fill back to the 7" casing shoe. Selectively perforate and sandwater fracture the Mesa Verde formation.

18. I hereby certify that the foregoing is true and correct

SIGNED

N. P. Buies

TITLE

Drilling Clerk

DATE

November 12, 1976

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

elad

*See Instructions on Reverse Side

RECEIVED

NOV 15 1976

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.