Form 3160-5 (November 1983 (Formerly 9-33	DEPART	UNITED STATES MENT OF THE INT U OF LAND MANAGEM		TRIPLICATE ctions on re-	Form approved. Budget Bureau I Expires August  5. LEASE DESIGNATION SF 078138	31, 1985	
(Do not		CES AND REPORT als to drill or to deepen or p TION FOR PERMIT—" for st		servoir.	6. IF INDIAN, ALLOTTEE	OR TRIBE NAME	
OIL WELL	GAS X OTHER			7	7. UNIT AGREEMENT NA	M S.	
2. NAME OF OPE	BATOR		Minor		8. FARM OR LEASE NAM	E	
El Paso 3. ADDRESS OF O	Natural Gas C	ompany			Morris 9. Wall No.		
P.O. Bo	x 4289. Farmin	gton. New Mexico	87499		#4		
4. LOCATION OF See also space	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)					WILDCAT	
	990'S, 990'W RECEIVED  MAR 18 (985				Aztec Pictured Cliffs 11. SEC, T., E., M., OR BLK. AND SURVEY OR AREA		
14. PERMIT NO.		15. ELEVATIONS (Show wheth	er DE RT GR etc.	or ore	Sec. 28, T30	N, R11W NMPM	
		5971' GL	and office and processing the second		San Juan	New Mexico	
16.	Check Ap	propriate Box To Indica	te Nature of Natice. I	Report, or O		NOW MOKIES	
	NOTICE OF INTEN			•	UBNT REPORT OF:		
TEST WATER FRACTURE TR SHOOT OR AC REPAIR WELL	IDIZE A	CLL OR ALTER CASING IULTIPLE COMPLETE BANDON* HANGE PLANS	WATER SHUT-C FRACTURE TRE SHOOTING OR (Other)	ATMENT	REPAIRING W ALTERING CA ABANDON MEN	SING	
(Other)			Completi	ion or Recomple	of multiple completion of tion Report and Log for	m.)	
proposed w nent to this	Ork. II Wen is direction	RATIONS (Clearly state all per- nally drilled, give subsurface	tinent details, and give pe locations and measured ar	ertinent dates, i nd true vertical	including estimated date depths for all markers	of starting any and zones perti-	
Recon	mended Procedu	re to plug and ab	andon:				
1) M	Move on locatio	n and rig up - ci	rculate wellbore	е.	·		
		ment plug from 19 formations. WOC		cover the	e Fruitland and	1	
7` ´ s	Spot a 35 sx (4 into the squeez	neeze holes 50' be 1.3 cu. ft.) ceme e hole leaving a 6'. WOC 6 hours.	nt plug. Presso cement plug ins	ure displa	ace 13 sx (15.3	34 cu.ft.)	
		meeze holes 50' be sx (82.6 cu.ft.)			surface		
5) (	Cut off wellhea	d and install a d	ry hole marker.		DECE	ש	
					MAR 2	1900	
					OIL CON	•	
_	fy that the foregoing is	true and correct					
signed 🚣	ren w Foll	hurgell TITLE_	Sr. Production	Engineer	DATE March	18, 1985 OVED	
(This space fo	or Federal or State office	e use)			AS AM	ENDFD	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:					DATE	4.4005	
	E ATTACHED FOR				MAR 2	1 1985	
	TIONS OF APPRO	八	ions on Reverse Side		Farth. MILL	ENBACH	

OF APPROVAL \*See Instructions on Reverse Side NMOCC

AREA MANAGER

## Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures, and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions, Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid coutents not sealed off by cement or otherwise; depths (top and bottom) and method of plucement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

# PRIVACY ACT

The Privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et. seq., 351 et. seq., 25 U.S.C. et. seq.; 43 CFR 3160. PRINCIPAL PURPOSE: The information is to be used to evaluate, when appropriate, approve applications, and report completion of secondary well operations, on a Federal or Indian lease.

ROUTINE USES: (1) Evaluate the equipment and procedures used during the proposed or completed subsequent well operations. (2) Request and grant approval to perform those actions covered by 4.3 CFR 3162.3-2(2). (3) Analyze future applications to drill or modify operations in light of data obtained and methods used. (4)(5) Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, eriminal or regulatory investigations or prosecutions.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this notice and report and disclosure of the information is mandatory once an oil or gas well is drilled.

The Paperwork Reduction Act of 1980 (44 U.S.C. 3501, et. seq.) requires us to inform you that:

This information is being collected in order to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

This information will be used to report subsequent operations once work is completed and when requested, to obtain approval for subsequent operations not previously authorized.

Response to this request is mandatory for the specific types of activities specified in 43 CFR Part 3160.

### BUREAU OF LAND MANAGEMENT Caller Service 4104 Farmington, New Mexico 87499

Attachment to Notice of

Re: Permanent Abandonment

Intention to Abandon

Well: 4 Morris

::..\_

#### CONDITIONS OF APPROVAL

- 1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."
- 2. The Farmington office (telephone (505) 325-4572) is to be notified in sufficient time for a representative to witness all plugging operations.
- 3. Blowout prevention equipment is required.
- 4. In addition to normal filling of pits and cleanup of location, additional surface restoration work may be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Surface Management Agency for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
- 5. The following modifications to your plugging program are to be made (when applicable):

The plug in item 3 is extended to cover the interval from 1030' to 870' in order to cover the the top and bottom of the 0jo Alamo.

You are further advised that any instructions, orders or decisions issued by the Eureau of Land Management are subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.

Office Hours: 7:45 A.M. to 4:30 P.M.

#### GENERAL REQUIREMENTS FOR PERMANENT ABANDONMENT OF WELLS ON FEDERAL LEASES FARMINGTON RESOURCE AREA

- 1. Secure prior approval before changing the approved plugging program.
- 2. Plugging equipment used shall have separate mixing and displacement pumps and a calibrated tank to assure proper displacement of plugs.
- 3. A proper tank or pit will be used to contain all fluids pumped from the well during plugging operations.
- 4. All cement plugs are to be placed through tubing (or drillpipe) and shall be a minimum of 15 sacks or 100 feet in length, whichever is greater.
- 5. Any cement plug placed when well is not full of fluid, or when well may be taking fluid, will be touched after cement has set to verify proper location.
- 6. Mud must be placed between plugs. Minimum consistency of plugging mud must be 9.2 lbs/gal. Brine is to be utilized for mixing mud where possible.
- 7. Within 30 days after plugging work is completed, file Subsequent Report of Abandonment, Form 3160-5 (formerly 9-331), in quintuplicate with Area Manager, Bureau of Land Management, Caller Service 4104, Farmington, New. Mexico 87499. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.
- 8. All permanently abandoned wells are to be marked with a permanent monument, on which has been stenciled or beaded the well name, well number, and well location by quarter-quarter, section, township and range. The monument is to be of steel pipe, not less than four inches in diameter, cemented permanently in the ground, and extending four feet above general ground level. The top should be closed with a screw cap, welding, or a cement plug.
- 9. After plugging work is completed:
  - Fill all pits, rat hole and cellar. 8.
  - Clean well location of all equipment, concrete bases, pipe, junk and ъ.
  - Cut or remove tie downs.
- If last well on lease, and no additional drilling is contemplated, fill tank battery pits, remove battery equipment, and clean and level battery location.
- Accomplish surface restoration as specified by the surface management agency or land owner.

All above are minimum requirements. The Subsequent Report of Abandonment will not be approved and the period of liability under the bond of record terminated until the lease is inspected and surface work approved.

Please advise this office when the well location is ready for final inspection.

You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.

Form 3160-5 (November 1983)

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

### UNITED STATES

SUBMIT IN TRIPLICATE. (Other instructions on re-

Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

X

F	BUREAU OF LAND MANAGEMENT	5. LEASE DESIGNATION AND SERIAL NO.  SF 078138
	SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
١.	OIL GAS MAY 1 (1985	7. UNIT AGREEMENT NAME
2.	NAME OF OPERATOR	8. FARM OR LEASE NAME
<u>.</u>	El Paso Natural Gas Company FARMINGTON RESOURCE AREA	Morris
	PO Box 4289, Farmington, NM 87499	4
i.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT AZTEC P. C.
	990's, 990'w,	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NMPM
		Sec.28, T30N, R11W
4.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	5971' GL	San Juan N.M.
6.	Check Appropriate Box To Indicate Nature of Notice, Report, or O	ther Data
	NOTICE OF INTENTION TO:	ENT REPORT OF:

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

5-10-85 Move on location and rigged up.

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

5-13-85 Pulled old tubing string and ran new work string. a 85 sx (100.3 cu. ft.) cement plug from 1930 to 2330' to cover the Fruitland and Pictured Cliff formations. W.O.C.

5-14-85 Tagged top of cement @ 1836'. Perforated 4 squeeze holes @ 1030'. Spotted a 55 sx (64.9 cu.ft.) cement plug. Pressure displace 22 sx (26 cu. ft.) of cement into squeeze holes. Leaving a cement plug from 858 to 1030 inside and outside the casing. W.O.C. 6 hours Tagged cement @ 838'. Perforated 4 squeeze holes at 183'. Circulated a 70 sx (82.6 cu.ft.) cement plug back to surface.

5-15-85 Cut off wellhead and installed dry hole marker with 6 sx of cement.

18. I hereby certify that the foregoing is true and correct		
	TITLE Production Engineer	DATE May 17, 1985
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	Frankeller
MAY 23 1985	/2	

OIL CON. DIV. \*See Instructions on Reverse Side