

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan  
 Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 3-10-64  
 Company PAN AMERICAN PETROLEUM CORP. Lease Buff Gas Unit "C" Well No. 1  
 Unit B Sec. 27 Twp. 30N Rge. 12W Purchaser \_\_\_\_\_  
 Casing 4-1/2 Wt. 10.5 I.D. 4.025 Set at 6365 Perf. 6152-62 To 6220-48  
 Tubing 2-3/8 Wt. 4.7 I.D. 1.995 Set at 6167 Perf. Open To Ended  
 Gas Pay: From 6152 To 6246 L 6200 xG .700 -GL 4340 Bar.Press. \_\_\_\_\_  
 Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single  
 Date of Completion: 4-1-64 Packer None Reservoir Temp. \_\_\_\_\_  
 Single-Bradenhead-G. G. or G.O. Dual

OBSERVED DATA

Tested Through (None) (Choke) (None) Type Taps Flange

| No. | Flow Data            |                        |             |                      |           | Tubing Data |           | Casing Data |           | Duration of Flow Hr. |
|-----|----------------------|------------------------|-------------|----------------------|-----------|-------------|-----------|-------------|-----------|----------------------|
|     | (Prover) (Line) Size | (Choke) (Orifice) Size | Press. psig | Diff. h <sub>w</sub> | Temp. °F. | Press. psig | Temp. °F. | Press. psig | Temp. °F. |                      |
| 1.  | 9 days<br>2 inch     |                        | 201         |                      |           | 1901        | 50° est.  | 1901        | 48        | 3 hrs.               |
| 2.  |                      |                        |             |                      |           |             |           |             |           |                      |
| 3.  |                      |                        |             |                      |           |             |           |             |           |                      |
| 4.  |                      |                        |             |                      |           |             |           |             |           |                      |
| 5.  |                      |                        |             |                      |           |             |           |             |           |                      |

FLOW CALCULATIONS

| No. | Coefficient (24-Hour) | $\sqrt{h_w P_f}$ | Pressure psia | Flow Temp. Factor F <sub>t</sub> | Gravity Factor F <sub>g</sub> | Compress. Factor F <sub>pv</sub> | Rate of Flow Q-MCFPD @ 15.025 psia |
|-----|-----------------------|------------------|---------------|----------------------------------|-------------------------------|----------------------------------|------------------------------------|
| 1.  | 12.3690               |                  | 213           | 1.000                            | .9258                         | 1.026                            | 2302                               |
| 2.  |                       |                  |               |                                  |                               |                                  |                                    |
| 3.  |                       |                  |               |                                  |                               |                                  |                                    |
| 4.  |                       |                  |               |                                  |                               |                                  |                                    |
| 5.  |                       |                  |               |                                  |                               |                                  |                                    |

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
 Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
 F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-S</sup>)  
 Specific Gravity Separator Gas \_\_\_\_\_  
 Specific Gravity Flowing Fluid \_\_\_\_\_  
 P<sub>c</sub> 1913 P<sub>c</sub><sup>2</sup> 3,699,569

| No. | P <sub>w</sub> P <sub>t</sub> (psia) | P <sub>t</sub> <sup>2</sup> | F <sub>c</sub> Q | (F <sub>c</sub> Q) <sup>2</sup> | (F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-S</sup> ) | P <sub>w</sub> <sup>2</sup> | P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup> | Cal. P <sub>w</sub> | P <sub>w</sub> /P <sub>c</sub> |
|-----|--------------------------------------|-----------------------------|------------------|---------------------------------|--|-----------------------------|--|---------------------|--------------------------------|
| 1.  |                                      |                             |                  |                                 |  | 230,000                     | 3,499,569  |                     |                                |
| 2.  |                                      |                             |                  |                                 |  |                             |  |                     |                                |
| 3.  |                                      |                             |                  |                                 |  |                             |  |                     |                                |
| 4.  |                                      |                             |                  |                                 |  |                             |  |                     |                                |
| 5.  |                                      |                             |                  |                                 |  |                             |  |                     |                                |

Absolute Potential: 2638 MCFPD; n .75  
 COMPANY PAN AMERICAN PETROLEUM CORPORATION  
 ADDRESS Box 400, Farmington, New Mexico  
 AGENT and TITLE F. L. Nabors, District Engineer  
 WITNESSED by F. W. Poell  
 COMPANY F. W. Poell

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- $Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.
- $P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia
- $P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia
- $P_f$  = Meter pressure, psia.
- $h_w$  = Differential meter pressure, inches water.
- $F_g$  = Gravity correction factor.
- $F_t$  = Flowing temperature correction factor.
- $F_{pv}$  = Supercompressibility factor.
- $n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .