

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-045-09137
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name McCARTY
8. Well No. 1
9. Pool name or Wildcat FULCHER KUTZ -PICTURED CLIFF

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator NORMAN L. GILBREATH
3. Address of Operator P.O. BOX 208, AZTEC, NEW MEXICO 87410	4. Well Location Unit Letter M : 970 Feet From The SOUTH Line and 660 Feet From The WEST Line Section 28 Township 30N Range 12W NMPM SAN JUAN County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-25-96 BUILT ROAD TO LOCATION-- DUG WATER PIT
6-26-96 MOVED RIG IN. PULLED RODS AND PUMP. SPOTTED 58 SXS CLASS B
2% CACL AND FLRSEAL AT 1590'--RIGGED WIRELINE--TAGGED CEMENT
AT 1036' PERF 2 SHOTS AT 950' NO CIRCULATION TO SURFACE.
CONTACTED E. BUSCH AT NMCD--ORDERED TO SHOOT AT 650' UNSTD
BRIDGE PLUG(5½") MODIFIED WELLHEAD--PERFORMED SUICIDE SQUEEZE
AT 950' SQUEEZED 65 SXS UNDER PRESSURE BACKUP AT 700# .UNSTD
PACKER--SPOTTED 20 SXS CEMENT. PULLED OUT OF HOLE. TAGGED
CEMENT AT 466'--2 SHOTS AT 84' SQUEEZED 34 SXS OUTSIDE
5½" AT 200 PSI SPOTTED 10 SXS INSIDE 5½" FROM 84' TO SURFACE.
6-27-96 SET MARKER, COVERED PIT AND RESTORED LOCATION

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Norman L. Gilbreath TITLE OPERATOR DATE 7-25-1996
TYPE OR PRINT NAME NORMAN L. GILBREATH TELEPHONE NO. 632-8845

(This space for State Use)

APPROVED BY Conrad Cardoux TITLE Deputy O&G Inspector DATE 7-31-96
CONDITIONS OF APPROVAL, IF ANY: P.M.O.C.O