

RECEIVED

AUG 18 1952

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Line

OIL WELL SERVICE CO.

RECEIVED

AUG 30 1952

OIL CON. COM.
DIST. 3

TEMPERATURE SURVEY

LOCATION

COMPANY

FILE

WELL

FIELD

COUNTY

STATE

SEC

TWP

SURVEY

WELL
FIELD
COUNTY

STATE

FILE

Type of Survey

Log Measured From

Drilling Measured From

Permanent Datum

Elevation

Elevation

Elevation

Date of Cementing

Date of Survey

Amount of Cement

Amount of Admix

Time

Time

Type

Type

Casing Size

from

from

Casing Depth

to

to

Diam of Hole

8-8.5" from

Depth

RECEIVED

AUG 18 1952

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

OIL WELL SERVICE CO.

RECEIVED

AUG 30 1952

OIL CON. COM.
DIST. 3

TEMPERATURE SURVEY

LOCATION

COMPANY

WELL

FILE

FIELD

COUNTY

SEC. 17
SURVEY

TWP. 36N. RGE. 9E

STATE

DEGREE

WELL
FIELD
COUNTY

Type of Survey

Log Measured From

Drilling Measured From

Permanent Datum

Date of Cementing

Date of Survey

Amount of Cement

Amount of Admix

Elevation

Elevation

Elevation

Time

Time

Type

Type

Casing Size

from

from

Casing Depth

to

to

Diam of Hole

8-8.1/4" from

Depth

RECEIVED

AUG 18 1952

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

OIL WELL SERVICE CO.

RECEIVED

AUG 30 1952

OIL CON. COM.
DIST. 3

TEMPERATURE SURVEY

LOCATION	COMPANY	FILE	COUNTY	WELL	FIELD	STATE
	WELL	FILE				
	FIELD					
	COUNTY	STATE				
	SEC	TWP	RGE			
	SURVEY					
Type of Survey	TEMPERATURE SURVEY					
Log Measured From	Elevation					
Drilling Measured From	Elevation					
Permanent Datum	Elevation					

Date of Cementing	JUL 30, 1952	Time	1:11 PM
Date of Survey	JUL 30, 1952	Time	3:30 PM
Amount of Cement	200 SACKS	Type	
Amount of Admix	3-1008725	Type	

Casing Size	Casing Depth	Diam of Hole	Depth
2" from	to 4,100'	8-3/4" from	to
from	to	from	to
Survey Begins at	1,800'	Ft. Ends at	4,045' Ft.
Approx. Fill-Up	ON 100'	Max. Temp.	103 ON 4,045' Ft.
Run No.	1	Approx. Top Cement	1,470' Ft.
Recorded by	PETERSON	Witnessed by	W. D. HALL

REMARKS OR OTHER DATA

Approx. Fill-Up Based on Average of 1.1 cu. ft. per sack of set cement

ADMIX: 200 SACKS OF 50% CEMENT & 50% PEARLITE & GEL

TEMPERATURE IN DEGREES FAHRENHEIT







