Revised 12-1-55

OIL CON, COM.

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

[nit:	Undesig			-							
	ial	A	nnual		Speci	ial		_Date of	Test_ 9 _	26-60	
ompa	any Tema	Mations	1		Lease 0	overmen	*	Wel	l No	Λ	
nit	s	ec. 29	_Twp _	301 Rge	. <u>13W</u>	Purc	haser				
asiı	ng 4 W	t 11.6	_I.D	Set	at	26 Per	rf 583	3	Го <u>601</u>	1	
								f'			
as J	Pay: From_	5820 T	6011	L	x0	0.650			Bar.Pres	35	
							 -				
ate	of Complet	ion:	-	Single-B Packer Res				pe Well Marle-Ge Bradenhead-G. G. or G.O. Dual servoir Temp.			
	•	-		-,	OBSERVE			- i		· · · · · · · · · · · · · · · · · · ·	
este	ed Through	()) (Choke	·) (NOTE:				Type Tap	5		
			w Data			Tubing Data Press. Temp.		Casing Da		Dunakian	
		(Orific	e)	s. Diff.	I			Press.		of Flow	
[Size	Size	psi	g h _w		psig	°F.	psig 1937	[⊃] F•	Hr.	
						-/,-		- 1			
	20	3/4"	138		- 81			573		3 krs	
+											
					OT ONL OAT O	TIT A TOTAL					
_	Coeffici	FLOW CALCULATION Flow Temp.			Gravity Compress. Rate of Flow						
0.	(24-Hour) $\sqrt{h_{\mathbf{w}}p_{\mathbf{f}}}$		1		Fact	or	Factor	Facto:	r	Q-MCFPD 15.025 psia	
士		·	M, T								
	12.7650			190	0.9804		0.9608	1.013		1770	
		1									
Т											
T				PRI	ESSURE CA	LCU ATI	ONS				
		os shop. P	atio		ESSURE CA	ALCU ATIO		fic Gravit	ty Senai	rator Gas	
Livit	iquid Hydro	d Hydroca	arbons				Speci	fic Gravi	ty Separ	rator Gas ing Fluid	
Li	iquid Hydro	d Hydroca	arbons		cf/bbl.		Speci	fic Gravi	ty Separ ty Flow: PC 3.7	rator Gas ing Fluid	
Livit	iquid Hydro	d Hydroca	arbons (1-e ^{-s}	· · · · · · · · · · · · · · · · · · ·	cf/bbl. deg.	-	Speci Speci Pc	fic Gravi	P _C 3.7	ing Fluid	
Livit	iquid Hydro	d Hydroca	arbons		cf/bbl. deg.		Speci	fic Gravitic Gravitic Gravitic Pc-Pw	ty Separ ty Flow: PC 3.7	ing Fluid	
Livit	iquid Hydro Ly of Liquid P _w Pt (psia)	d Hydroca	arbons (1-e ^{-s}	· · · · · · · · · · · · · · · · · · ·	cf/bbl. deg.	Q) ²	Speci Speci Pc P _w 2	P _c -P _w	PC S.7	Pw Pc	
is Li	iquid Hydro	d Hydroca	arbons (1-e ^{-s}	· · · · · · · · · · · · · · · · · · ·	cf/bbl. deg.	Q) ²	Speci Speci Pc	fic Gravi	PC S.7	l. P _w	
S Li	iquid Hydro Ly of Liquid P _w Pt (psia)	d Hydroca	arbons (1-e ^{-s}	· · · · · · · · · · · · · · · · · · ·	cf/bbl. deg.	Q) ²	Speci Speci Pc P _w 2	P _c -P _w	PC S.7	Pw Pc	
Livit	Pw Pt (psia)	Pt Pt	F _c Q	(F _c Q) ²	cf/bbl.deg. (Fo	Q) ² (e-s)	Speci Speci Pc P _w 2	P _c -P _w	PC S.7	Pw Pc	
DOMPA DOMPA	Pw Pt (psia) Lute Porent	Pt Pt	F _c Q	(F _c Q) ²	cf/bbl.deg. (Foundation of the content of the cont	n 0.75	Speci Speci Pc P _w 2	P _c -P _w	PC S.7	Pw Pc	
DOMPA DOMPA TIME	Pw Pt (psia)	Pt Pt	F _c Q	(F _c Q) ²	cf/bbl.deg. (Foundation of the content of the cont	n 0.75	Speci Speci Pc P _w 2	P _c -P _w	PC S.7	Pw Pc	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q T Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- $P_{\mathbf{w}}^{-}$ Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- P_{f} Meter pressure, psia.
- $h_{\mbox{\scriptsize W}}\mbox{\footnotesize I}$ Differential meter pressure, inches water.
- F_g : Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.