

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/ ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Federal <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator El Paso Natural Gas Company	8. Farm or Lease Name LaPlata
3. Address of Operator PO Box 990, Farmington, NM 87401	9. Well No. 1 (P&A)
4. Location of Well UNIT LETTER M, 910 FEET FROM THE South LINE AND 905 FEET FROM THE West LINE, SECTION 29 TOWNSHIP 30N RANGE 13W NMPM.	10. Field and Pool, or Wildcat Basin Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 5455' GL	12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Due to a casing leak and non-production, it is planned to plug and abandon this well in the following manner:

Spot a 50 sk. cement plug to cover Dakota perforations (5820-6011').

Perforate squeeze hole opposite the Mesa Verde and spot 50 sks. cement at hole and pressure displace 30 sks. through hole.

Shoot off 4 1/2" casing at free point and spot a 75 sks. cement plug on casing stub (plug to cover the Pictured Cliffs).

Spot a 25 sk. cement plug at the base of the surface pipe.

Spot a 15 sk. cement plug at the surface with a Plug & Abandoned marker, clean location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed F. H. WOOD

Petroleum Engineer

March 14, 1972

SIGNED _____ TITLE _____ DATE _____

Original Signed by A. R. Kendrick

PETROLEUM ENGINEER DIST. NO. 3

DATE _____

APPROVED BY _____

TITLE _____

CONDITIONS OF APPROVAL, IF ANY: