

November 3, 1950

United States Geological Survey
Roswell, New Mexico

Attention: P. T. McGrath

Gentlemen:

Our Payne No. 1, San Juan County,
New Mexico was spudded on October 24, 1950.
177.73' of 13-3/8" surface casing was cemented with
200 sacks by Halliburton Oil Well Cementing Corp.,
and pressure was held at 600# for 15 minutes.
Top of casing was set 1 1/2' below surface and cementing
was completed at 5:00 a.m., October 26.

Circulation was lost at 2260' on
October 31, but regained on November 1. On November
2 a core was taken with a 7" core barrel at 2340-49
with a recovery of 7'-2", 1" being shale and 7'-1"
being sand, grey, hard and tight with a show of gas.
On November 2 another core was being taken, the re-
sults of which will be reported to you later.

Our letters giving you the progress
of this well will be formally reported to you as
soon as the forms are received from your office.

Sincerely yours,



Dolores Daniel
Secretary to
A. M. Lloyd

/daniel

cc: Mr. Al Greer
New Mexico Oil Conservation Commission
Aztec, New Mexico

NOTE: The following

is a list of the names of the
persons who have been
admitted to the

of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the

of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the

of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the

of the of the of the of the

Handwritten signature
of the of the of the of the
of the of the of the of the
of the of the of the of the

of the of the of the of the

of the of the of the of the
of the of the of the of the
of the of the of the of the
of the of the of the of the