

5 BLM 1. File  
**UNITED STATES**  
**DEPARTMENT OF THE INTERIOR**  
**BUREAU OF LAND MANAGEMENT**

**SUBMIT IN TRIPLICATE\***  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR  
Dugan Production Corp.

3. ADDRESS OF OPERATOR  
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface 1730' FSL - 1800' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
5499' GL; 5512' RKB

5. LEASE DESIGNATION AND SERIAL NO.  
NM 0206994

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Carpenter

9. WELL NO.  
1

10. FIELD AND POOL, OR WILDCAT  
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 25, T30N, R14W, NMPM

12. COUNTY OR PARISH  
San Juan

13. STATE  
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☒  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☐

REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well has an apparent casing leak. We plan to repair the casing as follows:

1. Set drillable bridge plug on wireline above perforations.
2. Hunt for hole with packer.
3. Squeeze hole in casing with cement. The amount to be determined after finding casing leak.
4. Drill out cement and bridge plug and restore well to production.

Notify this office within five days of production start-up.

**RECEIVED**

MAR 05 1985

OIL CON. DIV.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Jim L. Jacobs*  
Jim L. Jacobs

TITLE Geologist

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

DIST. 3 APPROVED

DATE 4/23/85

FEB 23 1985  
*John H. Miller*  
John H. MILLERBACH  
AREA MANAGER

\*See Instructions on Reverse Side