



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 080597
Unit Cartner

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			
Notice of Intention to Re-Work	X		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 31, 1961

Well No. 2 is located 1650 ft. from [N] line and 1500 ft. from [E] line of sec. 28
NE/4 Sec. 28 30N 8W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesa Verde San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6132 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is intended to workover this well in the following manner:

1. Set 2" tubing choke at approximately 4665'.
2. Move rig in, rig up and set blow out preventer.
3. Pull tubing.
4. Run McCullough casing survey to 4528' and if well is not wet run Lane Wells Potential Casing Survey to 4528'.
5. Set a drillable magnesium bridge plug at approximately 3050'.
6. By use of Fullbore packer, determine location of casing leak.
7. Squeeze casing leak with sufficient volume of HYS-400 cement tailing in with 50 sacks regular cement containing 2% calcium chloride to circulate cement to surface. W.O.C. 18 hours.
8. Drill cement and test casing with 2000#.

(Over)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 990

Farmington, New Mexico

By Original Signed D. W. Meehan

Title Petroleum Engineer

9. Drill bridge plug and clean out to total depth 5361' using gas.
10. Run temperature log.
11. Run 5 1/2" liner with turned down couplings and a Burns casing hanger with Neoprene seal.
12. Cement with 50 sacks regular, 1/4 cu. ft. fine Gilsomite/sk., 4 1/2 gal, and 1/8# flocc/sk. W.O.C. 18 hours.
13. Clean out to top of liner, test with 2000#.
14. Clean out to C.O.T.D. according to perforating log.
15. Perforate and frac as per logs.
16. Clean out to C.O.T.D. & test.
17. Run tubing and complete.
18. Clean location and release rig.