Denny & Fout DEPUTY OIL & GAS INSPECTOR

DEC 221997

Meter Number: 70312

Location Name: ELLIOT GAS COM H#1

Location:TN-30 RG-09 SC-26 UL-B

NMOCD Zone: OUTSIDE Hazard Ranking Score: 00

2 - Federal

DEGETYER APR 1 4 527

RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

Sandstone 10^{-9} to 10^{-13} cm/sec Shale 10^{-12} to 10^{-16} cm/sec Clay 10^{-12} to 10^{-15} cm/sec

Based on this information, the residual hydrocarbons should not migrate to groundwater.

Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.

TOTAL HAZARD RANKING SCORE: ____

_O____POINTS


Remarks: REDUNE & TOPO SHOW LOCATION OUTSIDE V.Z. THREE PITS ON LOCATION. LINUSED DEHY PIT BELONGS TO EPNG. WILL CLOSE PIT.

EMAE

ORIGINAL PIT LOCATION

Original Pit : a) Degrees from North 300 Footage from Wellhead 136

b) Length : 19' Width : 17' Depth : 2'



PHOTOS-1513

Completed By:

Signature

2.21.95

Date

FIELD PIT REMEDIATION/CLOSURE FORM

GENERAL	Meter: 70312 Location: Elliot 645 con H H Coordinates: Letter: B Section 26 Township: 30 Range: 9 Or Latitude Longitude Date Started: 2-28-95 Run: 10 33
FIELD OBSERVATIONS	Sample Number(s): Sample Depth: 12' Feet Final PID Reading 513 PID Reading Depth 2' Feet Yes No Groundwater Encountered
CLOSURE	Remediation Method: Excavation
KEMAKKS	Remarks: Accived Dug sanfle 1601e Soil Gray strong HYDrocarbon odor Signature of Specialist: Moyar Killian

10/31/50 (101502)



FIELD SERVICES LABORATORY ANALYTICAL REPORT

PIT CLOSURE PROJECT - Soil Samples Outside the GWV Zone

SAMPLE IDENTIFICATION

					-	
ŗ	Field	Lab ID				
SAMPLE NUMBER:	SAMPLE NUMBER: MK 41			946715		
MTR CODE SITE NAME:			N/A			
SAMPLE DATE TIME (Hrs):			1220			
SAMPLED BY:	N/A					
DATE OF TPH EXT. ANAL.:	5/3/95 N(A VG		3/3/95 NIA Gray sand & Chay			
DATE OF BTEX EXT. ANAL.:						
TYPE DESCRIPTION:						
R EMARKS :		RESULTS				
	·····	NESUL 13			···	
PARAMETER	RESULT	UNITS	DF	QUALIFIERS DF Q M(g) V(ml)		
TPH (418.1)	3220	MG/KG			2,07	28
HEADSPACE PID	513	РРМ				
PERCENT SOLIDS	86.1	%		er ave		
		TPH is by EPA Metho	od 418.1			
arrative:						
F = Dilution Factor Used						
Annual Bu	2		Date:	另一	20-45-	
pproved By:	1					

Perkin-Elmer Model 1600 FT-IR Analysis Report Sample identification 246713 Initial seasons sample: q = 1.070Volume of sample after extraction, all 18.000 Petroleum sydroparbors, pom TD17.bt5 | Met absorvence of hydroparbons | IPDC prop 1.415 The Reference of European Companies of the officers T-12 1399 1908 1909