

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

RECEIVED
MAR 26 1998

98 MAR 19 PM 1:22
070 FARMINGTON, NM

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL CON. DIV.
DIST. 3

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FNL, 990' FEL, Sec. 25, T-30-N, R-11-W, NMPM

5. Lease Number

SF-078198

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

Albright A #1

9. API Well No.

30-045-09236

10. Field and Pool

Basin Fruitland Coal/
Aztec Pict. Cliffs

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

2-16-98 MIRU. TOOH w/94 5/8" rods & pump. ND WH. NU BOP. TOOH w/76 jts 2 3/8" tbq.

TIH, tag CIBP @ 2480'. Establish circ. Plug #1: pump 33 sx Class "B"

neat cmt inside csg @ 2200-2480'. Reverse circ tbq & csg clean w/20 bbl

wtr. TOOH. SDON.

2-17-98 TIH w/gauge ring to TOC @ 2251'. PT csg to 500 psi, failed. TOOH. TIH, perf 3 sqz holes @ 2200'. TOOH. TIH w/cmt retainer, set @ 2157'. TOOH. Establish injection. Plug #2: pump 47 sx Class "B" neat cmt below cmt retainer outside csg. Pump 10 sx Class "B" neat cmt above cmt retainer inside csg @ 2100-2200'. TOOH. TIH, perf 3 sqz holes @ 1400'. TOOH. TIH w/cmt retainer, set @ 1350'. TOOH. Establish injection. Plug #3: pump 72 sx Class "B" neat cmt below cmt retainer outside csg. Pump 25 sx Class "B" neat cmt above cmt retainer inside csg @ 1177-1400'. TOOH. Establish circ down csg & out csg valve. Plug #4: pump 85 sx Class "B" neat cmt down csg & out csg valve. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Fill csg w/20 sx Class "B" neat cmt. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 2-17-98. (J. Morris, BLM on location for plugging).

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 3/17/98

(This space for Federal or State Office use)

APPROVED BY [Signature] Title

Date MAR 24 1998

CONDITION OF APPROVAL, if any:

NMCCD