MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

	6.400							
	Form C-122							
R	evised 12-1-55							
San Ju								
st1	-9-64							
	•							
No	1.							
al Cas	Company							
630	2							
625								
°								
ar.Press. 12.0								
or G.O. Dual								
. or G	.U. Dual							
<u> </u>								
ta Temp.	Duration							
-	of Flow							
°F.	Hr.							
	20 days							
	3 hrs.							
								
	<u> </u>							
35.	Rate of Flow							
r	Q-MCFPD 15.025 psia							
5	<u> 1293</u>							
tu Sen	arator Gas							
ty Flo	arator Gas wing Fluid							
p2_	106k.h							
								
1	1 i							

or -	Basin Dak		r (J. 11 (1.1 (1.1 (1.1 (1.1 (1.1 (1.1 (1.1	<i>r</i> 1 •	_ 1		Date of To	est l	-96la	
itia	1 1	Annu	al		Speci	.al		pate of 1	N-	-9-6l4	
npar	y Souther	n Union Pr	roducti	on Co. L	ease	MC G		Mell	NO	2	
it _	B Se	c. 27 Tw	р. 30-1	Rge	. <u>13-W</u>	Purch	aser_El	Paso Natur	al Cas	Company	
sina	4-1/2 Wt	. 10.50 I	.D. 4. 0	52 Set	at 640	4 Per	f. 5122	T	<u>630</u>	2	
hine	1-1/2 Wt	. 2.90 I	.D. 1.6	510 Set	at 625	O Per	f. 6240	T	<u>625</u>	0	
- De	ay: From_	6199 To	6302		21x0 x(730	<u>-</u> GL	4555 _B	ar.Pres	12.0	
5	ing Thru:	Casing		ብ ተ	ni nø	TT	Type We	ll Sin	gle Ges	l	
oduo	ing Thru:	casing		D 3	······································	Sing	le-Brade	head-G. G	. or G	.O. Dual	
te d	of Completi	on: <u>12-</u> 2	0-63	Packer			neservo.			and the second s	
					OBSERV	ED DATA					
ste	d Through	(Prover)	(Choke)	Meters				Type Taps			
		Flow I	Data			Tubing	Data	Casing Da	ta Tem	Duratio	
	(Prover)	(Choke) (Orifice)						Į.		of Mio	
1	Size	Size	psig	hw	°F.	psig	^O ₽,	psig			
上					700	2009 358	700	1978 1537		20 days	
╀	2*	3/4	358		700	330					
1											
+											
						CULATION		10		Pote of Flow	
- 1	00011101011			Pressure Flow Temp.		Temp.	Gravity Compre Factor Factor		Rate of Flow Or Q-MCFPD		
•	(24-Hour)		hwp _f psia		Ft		Fg	Pq 1		15.025 psi	
1	12.3650			370	.990	£	.9066	1.04	5	1,293	
$\cdot \top$											
. [זמ	क्षाक्षक	CALCUTATI	ONS				
								ific Cravi	tv Sen	arator Gas	
s L	iquid Hydro ty of Liqui	carbon Rat	cio		_ cf/bb# deg	•	Spec	ific Gravi	tv Flo	wing Fluid	
~ • -			_(1-e ^{-s})		-	P _c	2021	Pc	HOOK A	
	$P_{\mathbf{W}}$	P _t .	F _c Q	(F _c Q)	2 ($F_cQ)^2$ $1-e^{-s}$	P _w 2	$P_c^2 - P_w^2$	1	al. P	
	Pt (psia)	, t	- c -	1	(1-e-s)	2399.4	1685.0		P _w P _c	
										CEPENA	
										ARLULIY	
										JAN 2 8 19	
	lute Poten	tial:	8337); n	75		1	01 02 VIAU 2 MC2 UO /	
bsc	ANY Sout	Box 808	+ FATE	ington	er mou	0	Original Sign	ed By		C CIST	
bsc	ESS P.O									\	
DSC COMF ADDR	NESS P.O NT and TITL NESSED	E Verne	Roekto	ld, Jr.	Ingineer	<u> </u>	VERNE RO	CKHOLD			

(1) Mr. Paul Clote
(1) El Paso Matural Gas Co., Proration Dept.
P.O. Box 1492, El Paso, Texas
(2) Mr. H. L. Kindricks, P.O. Box 990, Farmingto n, New Maxico
(1) File

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- F_{g} Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n _ Slope of back pressure curve.

Note: If $P_{\mathbf{W}}$ cannot be taken because of manner of completion or condition of well, then $P_{\mathbf{W}}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\mathbf{t}}$.