

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

**RECEIVED
BLM**

Sundry Notices and Reports on Wells

95 MAY 17 PM 2:59

1. Type of Well
GAS

RECEIVED
MAY 22 1995

070 FARMINGTON, NM

5. Lease Number
SF-078201A
6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

2. Name of Operator

MERIDIAN OIL OIL CON. DIV.
DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

800' FSL, 1090' FWL, Sec. 24, T-30-N, R-9-W, NMPM

8. Well Name & Number
Riddle A #3

9. API Well No.
30-045-09276

10. Field and Pool
Blanco Mesaverde

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent	☐ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - Bradenhead repair	

13. Describe Proposed or Completed Operations

5-10-95 MIRU. SDON.
5-11-95 ND WH. NU BOP. TOO H w/150 jts 2 3/8" tbq. TIH w/gauge ring to 4785'. Set RBP @ 4000'. Dump sd on top of RBP. RU, latch onto 4 1/2" csg. Ran free point to 3300'. Burn off 4 1/2" csg @ 2218'. TOO H w/68 jts 4 1/2" csg. SDON.
5-12-95 Load 7" csg w/100 bbl wtr. RU, ran CBL @ 0-2202', TOC @ 600'. Set 7" RBP @ 2150'. PT 7" csg to 1000 psi/15 min, OK. Perf 2 sqz holes @ 580'. RD. TIH w/FB pkr, set @ 420'. Establish injection. Pump 325 sx Class "G" cmt w/2% calcium chloride. Circ 5 bbl cmt to surface. Displace 1 bbl cmt below pkr. Bradenhead valve sqz w/1000 psi. SI. WOC. TOO H w/pkr. Reapply 1000 psi on sqz. SDON.
5-13-95 TIH w/mill, tag cmt @ 440'. Drill cmt @ 440-520'. TOO H w/mill. TIH, drill cmt @ 520-580'. PT 7" csg to 1000 psi/15 min, OK. TOO H. TIH w/retrieving head. Circ sd of RBP. TOO H w/RBP & retrieving head. SDON.
5-14-95 TIH w/mill. Dress top of 4 1/2" csg. TOO H w/mill. TIH w/69 jts 4 1/2" 10.5# K-55 STC csg patch, set @ 2204'. PT csg patch to 1000 psi/15 min, OK. TIH w/retrieving head, tag RBP @ 4000'. Blow well clean. Release RBP, TOO H. SDON.
5-15-95 TIH, tag fill @ 4775'. CO. TOO H. TIH w/150 jts 2 3/8" 4.7# J-55 tbq, landed @ 4636'. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed *[Signature]* Title Regulatory Affairs Date 5/15/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

MAY 17 1995

NMOCD

FARMINGTON DISTRICT OFFICE
BY *[Signature]*