

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells 94 JUL 20 PM 2:09

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
990'FSL, 1148'FWL, Sec.19, T-30-N, R-9-W, NMPM

070 FARMINGTON, NM

RECEIVED
JUL 25 1994

OIL CON. DIV.
DIST. 3

5. Lease Number
SF-077833A
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Mansfield #2
9. API Well No.
30-045-09280
10. Field and Pool
Blanco Mesa Verde
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input type="checkbox"/> Notice of Intent	<input checked="" type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Other -	

13. Describe Proposed or Completed Operations

7-8-94 MIRU. TOH w/tbg. Tbg stuck @ 4600'. Cut tbg off @ 4500'. POOH w/147 jts & 1 10' piece tbg. TIH w/7" csg scraper to 4374'. POOH w/csg scraper.
7-11-94 TIH w/7" cmt retainer to 4343'. Tried to PT, csg would not PT. Plug #1: pumped 223 sx Class "B" cmt below retainer, stung out of retainer, dumped 10 sx on top of retainer. LD tbg to 4247'. Pumped 53 bbl mud @ 2862-4247'. LD tbg to 2862'. Plug #2: pumped 30 sx Class "B" cmt @ 2697-2862'. TOH. SDON.
7-12-94 TIH, tag plug @ 2717'. Spot 7 bbl mud @ 2530-2717'. TOH. TIH, perf 2 holes @ 2530', TOH. TIH w/7" cmt retainer, set @ 2485'. Plug #3: pumped 33 sx Class "B" cmt below retainer & 27 sx on top of retainer, TOC @ 2382'. TOH to 2359'. Pumped 22 bbl mud @ 1782-2359'. TOH. TIH, perf 2 holes @ 1782', TOH. TIH w/7" retainer, set @ 1730'. Plug #4: pumped 59 sx cmt below retainer & 31 sx on top, top of cmt @ 1560'. LD tbg @ 1541'. Pumped 50 bbl mud @ 225-1541'. LD tbg to 188', TOH. TIH, perf @225', TOH. TIH w/7" retainer, set @ 188'. Stung out of retainer & circ good cmt out of csg & bradenhead. TOH.
7-13-94 ND BOP. Cut off wellhead & install dry hole marker w/33 sx cmt. RD Well plugged & abandoned 7-13-94.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 7/14/94

(This space for Federal or State Office use)

APPROVED BY

CONDITION OF APPROVAL, if any:

Approved as to plugging of the well bore. Date
Liability under bond is retained until
surface restoration is completed.

APPROVED

JUL 22 1994
Chip Haraden
for DISTRICT MANAGER

