Form C-122

J-OCC
I-H.L.Kendrick NEW MEXICO OIL CONSERVATION COMMISSION
1-Bill Parrish
1-TCA, 1-Snoddy
2-EPNG (El Paso, Farm.)
1-International
1-F

Revised 12-1-55

	1-1			MOLTI-	-POINT BA	ion presi	Cal anuc	. FUR GAS	METTE			
Pool	BASIN DAKOTA		TA	Formation			DAKOTA		County San		ian	
Initial X Ann			Annua	alSpecia			ial		_Date of	Test	3/31/64	
ompa	any Reta D	eve lop	ment (	Co	I	Lease	Cedar H	11	Wel	1 No	_1	
Init	_ <u>w</u> S	ec24	Twp	0. <u>30</u>	n Rge	9. <u>11 w</u>	Purch	naser	Paso Nat	ural Ga	s Co.	
											12'	
	_							•			ind	
	-											
											55. 12.0	
rod	ucing Thru:	Cas	ing		Tu	ongA	Sin	Type we gle-Brade	nhesd-G.	G. or G	.O. Dual	
ate	of Complet	ion:_	3/21,	/64	Packer	r	NI P	Reservo	ir Temp.	<del></del>		
						OBSERV	ED DATA					
est:	ed Through	(Prov	<b>er</b> ) (	Choke)	(Meter)				Type Tar	)s		
<del></del>			low Da	ata			Tubing Data		Casing Data			
T.	(Prover)	(Cho	ke)	Press	. Diff.					1	Duration of Flow	
	(Line) Size	Si	ze	psig	h <sub>w</sub>	°F.	psig	o <sub>F</sub> .	psig	°F.	Hr.	
3I		ļ					2373		2396	<del>-</del>	7 Days	
L.   2.	· <del></del>	3/	411	514	1	80	514	80	1591		3 Hp.	
3.												
••				ļ	<b></b>				<u> </u>	<del>                                     </del>		
5.		<u> </u>		<u> </u>				<u> </u>	L			
					· · · · · · · · · · · · · · · · · · ·	FLOW CAL	CULATION	s				
	Coeffici	cient		h <sub>w</sub> p <sub>f</sub> psia		Flow	Temp.	Gravity	Compress.		Rate of Flow	
No.	(24-Hour) 7		- / h			Factor F <sub>t</sub>			Factor F <sub>pv</sub>		Q-MCFPD <b>8</b> 15.025 psia	
_	(24-1100	V 'W						Fg	1-053			
2.	12.3650				526	.9813		9463	1.05	3	6,360	
3.												
<u>+•</u>												
5.			L			<del></del>						
					PR	ESSURE C	ITA IUSLA	ons				
						. 4				• • •		
	iquid Hydro ty of Liqui					cf/bbl. deg.					arator Gas wing Fluid	
cavi C	ty or Liqui	id nydi	rocaro )	1-e <sup>-8</sup> )		ueg.					5798.5	
<u> </u>								_	P <sub>w</sub> 1603 F			
		<del></del>		<del></del>					<del></del>			
No.	$P_{\mathbf{W}}$	P	2   F	· Q	$(F_cQ)^2$	· (1	(cQ) <sup>2</sup>	P. 2	$P_c^2 - P_w^2$	C	al. P.	
	Pt (psia)	- 1		C ·	,-U4)	נ)	_e-s )	*	"		$ \begin{array}{c c} P_{\mathbf{w}} & P_{\mathbf{c}} \\ \end{array} $	
<u>1.</u> 2.			二二					2569.6	3228.9		.665	
<u>₹•</u> [		<u> </u>							<del> </del>			
3. 4.		<b></b>	-+-				<del>+</del>			+		
4. 5.												
	lute Potent	tial:	0_8			MCFPD	n75		<u>-</u> -			
		_		it Co.								
	ESS 234	Petr.	Club	Plaza,	Farming							
	T and TITL				Product	ion Engi	Deer					
	ESSEDPANY			McAnal	cal Gas C	<u> </u>			<del></del>			
COM	ANT	<u>F</u>	T-F#8C	Natur		RE	MARKS		<del></del>	ZITI	11/2	
	-								, , , , ,	Kili	irt il	
									į		* HE # 1	
									\$ 	AHR 7	196	
									<b>\(\)</b>	JIL CO	er al	
									/	DIST	3	
										· ·	· •	

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- $P_c$  72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_{f}$  Meter pressure, psia.
- $h_{\mathbf{W}}^{-}$  Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\rm W}$  cannot be taken because of manner of completion or condition of well, then  $P_{\rm W}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\rm t}$ .