

3-OCC  
1-Bill Parish  
1-Tidewater, Durango  
2-Tidewater-Midland  
1-NW Prod. NEW MEXICO OIL CONSERVATION COMMISSION  
1-Lion  
1-Texas Nat'L.  
1-D  
1-F MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Form C-122  
Revised 12-1-55

Pool Undesignated Formation Mesaverde County San Juan  
Initial X Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 10-4-61  
Company Southwest Production Co. Lease Irene Brown Well No. 1  
Unit 0 Sec. 22 Twp. 30N Rge. 12W Purchaser El Paso Nat. Gas Co.  
Casing 4 1/2 Wt. 10.50 I.D. 4.040 Set at 3339 Perf. Open To Hole  
Tubing 1 1/2 Wt. 2.76 I.D. 1.610 Set at 3315 Perf. \_\_\_\_\_ To \_\_\_\_\_  
Gas Pay: From 3338 To 3375 L 3315  $\alpha_g$  .67  $\alpha_{GL}$  2221.0 Bar.Press. 12.0  
Producing Thru: Casing \_\_\_\_\_ Tubing X Type Well Single Gas  
Single-Bradenhead-G. G. or G.O. Dual  
Date of Completion: 9/23/61 Packer - Reservoir Temp. \_\_\_\_\_

OBSERVED DATA

Tested Through (Proven) (Choke) (Mux) Type Taps \_\_\_\_\_

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) ( <del>Proven</del> ) Size	Press. psig	Diff. $h_w$	Temp. $^{\circ}F$	Press. psig	Temp. $^{\circ}F$	Press. psig	Temp. $^{\circ}F$	
SI						1350		1350		7 day
1.		3/4	135		64	135	64	461		3 Hr.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor $F_t$	Gravity Factor $F_g$	Compress. Factor $F_{pv}$	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12-3650		147	.9962	.9463	1.016	1,741
2.							
3.							
4.							
5.							


PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
 $F_c$  \_\_\_\_\_ ( $1-e^{-s}$ )  
Specific Gravity Separator Gas \_\_\_\_\_  
Specific Gravity Flowing Fluid \_\_\_\_\_  
 $P_c$  1362  $P_c^2$  1855.0  
 $P_w$  473  $P_w^2$  223.7

No.	$P_w$ $P_t$ (psia)	$P_t^2$	$F_c Q$	$(F_c Q)^2$	$(F_c Q)^2$ ( $1-e^{-s}$ )	$P_w^2$	$P_c^2 - P_w^2$	Cal. $P_w$	$\frac{P_w}{P_c}$
1.						223.7	1631.3		.347
2.									
3.									
4.									
5.									

Absolute Potential: 1,917 MCFPD;  $n$  .75  
COMPANY Southwest Production Company  
ADDRESS 207 Petr. Club Plaza  
AGENT and TITLE G. L. Hoffman, Production Engineer  
WITNESSED \_\_\_\_\_  
COMPANY \_\_\_\_\_

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- $Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.
- $P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia
- $P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia
- $P_f$  = Meter pressure, psia.
- $h_w$  = Differential meter pressure, inches water.
- $F_g$  = Gravity correction factor.
- $F_t$  = Flowing temperature correction factor.
- $F_{pv}$  = Supercompressability factor.
- $n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .