



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 095075
Unit Govt. Relay

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	IX
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 14, 1962, 19__

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 20

SW 1/4 Sec. 20 (1/4 Sec. and Sec. No.) 20N (Twp.) 14W (Range) 101N (Meridian)
P. O. Drawer 330 (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 5540 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

SEE ATTACHED



RECEIVED
FEB 14 1962

U. S. GEOLOGICAL SURVEY
SANTA FE, N. M.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The British-American Oil Producing Company

Address P. O. Drawer 330, Farmington, N.M.

By Wes R. Stone

Title Field Superintendent

THE BRITISH-AMERICAN OIL PRODUCING COMPANY
GOVT. RILEY NO. 1
SW SW SECTION 20-30N-14W
SAN JUAN COUNTY, NEW MEXICO

2-7-42 Drilled to total depth of 5280. Went in hole and cut core no. 1 from 5280 to 5300 feet. Recovered 20' black silty shale. Core barrel jammed.

2-8-42 Went in hole with core barrel to cut core no. 2. Cored from 5300 to 5323. Recovered 23' black silty shale. Core barrel jammed.

2-9-42 Rigged up Schlumberger and ran Induction-Electric Log from TD to 4700, 4160 to 2990 and from 1400 to bottom of surface, detailed from TD to bottom of surface. Ran Sonic Caliper log from TD to bottom of surface.

2-10-42 Went in hole for DST No. 1. Packers failed due to fractures. Went in hole for DST No. 2 testing interval 5195 to 5232. Tool open 6 minutes, closed 30 minutes, open for one hour, closed for 30 minutes. Recovered 85' drilling mud. IHP 2908, IBIP 208, IFF 30, FFP 30, FBIP 204, FHP 2450. Laid down drill collars.

2-11-42 Went in hole open ended and plugged as follows:

100' cement plug - 4980 to 4880'

100' cement plug - 850 to 750'

10 sack cement plug at 290

10 sack cement plug to surface

Dry hole marker has been erected. Well is now plugged and abandoned.

FORMATION TOPS:

Pictured Cliffs - 1117

Pt. Lechert - 3990

Mansue - 3887

U. Gallup - 32 4548

L. Gallup - 5147

