Fo	rin	C-1	22
Revised	12	-1-5	5

				MULTI	-POINT B	ACK PRES	SURE TEST	FOR GAS	WELLS	•	nevised 22 2 7
Pool	BASI	N DAK	OT A	F	'ormation		DA	KOTA	_County	San	Tuen
[niti	al <b>X</b> _		_Annua	al		Spec	ial		_Date of :	re <b>st</b> _	2/1/64
Compa	ny <b>Bota i</b>	<u>evelo</u>	pment	Co.		Lease	Fr		Wel	l No	
Jnit	s	ec. <u>21</u>	Twp	o. <u>30</u> 1	Rg	e. <u>11 i</u>	Purch	naser	EPNG Co.		
Casin	8 4 1/2 W	t10	<u>50</u> I.	D. 4.0	040 Se	t at <u>67</u>	Per	f. 65	73'	ľo <u>67</u> :	32•
ľubin	g <u>2 3/8"</u> W	t. <u>4</u>	.70 I	D. <u>1.</u>	<b>995</b> _Se	t at 66	<b>96</b> Per	f. Op	on	ro <u>E</u>	nd
as P	ay: From_	65751	_To_6	732'	L61	<u>196</u> x	G_67		4493	Bar.Pre	ss. <u>12.0</u>
rodu	cing Thru:	Cas	sing	<u>.</u>	Tu	bing	X	_Type We	11	ngle -	Gas
)ate	of Complet	ion:			Packe	r	Sing	Zie-Brade Reservo	ir Temp	J. OF G	r.O. Dual
							ED DATA				
[este	d Through	XXXXX	neraly ((	Choke)	(Mecan)	K			Туре Тар	s	
			17 D				Tubing	Data	Casing D	a † a	<del></del>
	(Prover)	(Chc		Press	Diff.	Temp.			Press.	Temp.	Duration of Flow
No.	(Line) Size		ze	psig	h <sub>w</sub>	°F•			psig		Hr.
SI							1991		2060	ļ	7 Days
		3/	4"		161	71_	161	71	740		3 Hrs.
		<b> </b>			+						
•											
5.		<u> </u>				L	L			l	<u> </u>
					_	FLOW CAL	CULATION	s			
					ressure	essure Flow Temp. Gravit Factor Facto		Gravity Factor	y Compress. Rate of Flow r Factor Q-MCFPD		
10.	(24-Hou	r)	$\sqrt{h_{\mathbf{w}}}$		psia		t	Fg	Fpv	1	@ 15.025 psia
	12,3650		ΛM <sub>1</sub>	-1	173	.989		.9463	1.01		2,035
2.	160 30 30										
3。											
•										<u>-</u>	
<del></del> -			<u> </u>		PR	ESSURE (	CALCULATIO	ons			
										C	t Coo
	quid Hydro y of Liqui			0 <u></u>		cf/bbl.deg.	•				arator Gas wing Fluid
	y or niqui	-		1-e <sup>-8</sup> )			_	P <sub>c</sub>			4293.1
								Pw	752	P#2	365.5
No.	$P_{\mathbf{W}}$	P	2 F	eQ.	$(F_cQ)^2$	2 (1	<sub>7-0</sub> ) <sup>2</sup>	P <sub>w</sub> 2	$P_c^2 - P_w^2$	Ca	al. Pw
	Pt (psia)	- 1		c <b>-</b>	(-64)	()	(cQ) <sup>2</sup> L-e <sup>-s</sup> )				Pw Pc
1. 2. 3. 4.								565.5	3727.6	<del></del>	.363
3.						<del></del>					
										<del> </del>	
5.								<u> </u>	<u> </u>		
	ute Potent			261	<u> </u>	MCFPD:	; n <u>•75</u>				
	INY ESS	224 B	Develo	lub P	Leza. Far	ed poten	New Mex	ico			
AGEN'I	and TITLE	<u> </u>	Georg	المالة	ioffman,	Product	on Engin	199			
	ESSED				-		<del> </del>			ة ذ مو	
OPIPA	NY					RE	MARKS			1111.	VFN
									/{	<b>KLULI</b>	1
									į '		1964

OIL CON. COM. DIST. 3

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- Pc= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{w}}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- $F_t$  Flowing temperature correction factor.
- $F_{\mathrm{pv}}$  Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .