


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. 0443-B
Unit O. J. Hoover "A"



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

O. J. Hoover "A"

Farmington, New Mexico September 19, 1957

Well No. 1 is located 1780 ft. from N line and 913 ft. from Ex line of sec 23
SW/4 of Section 23 T-30-N R-16-W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5413 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth of this well was 10,808', DT, and was plugged back to 10,796'.
HOWCORTTS tool was set at 10,733'. Perforated with four shots per foot 10,877
to 10,788. Swab to 10,000', no show of gas or oil. Failed to acidize this zone.
This zone abandoned.

Perforate 10,655 to 10,700 with four shots per foot. Spotted 500 gallons acid
over these perforations and this zone was re-acidized with 200 gallons acid.
Cemented zone with 100 sacks of cement.

Perforate 10,592 to 10,640 with four shots per foot. Zone was acidized with 500
gallons acid. Cemented this zone with 100 sacks of cement.

Packer set at 10,445. Perforate 10,505-10,529 with five shots per foot. Acidize
with 500 gallons acid. Cemented zone with 100 sacks of cement. (See attachment)
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 487

Farmington, New Mexico

ORIGINAL SIGNED BY
D. J. SCOTT

By _____

Title Field Clerk

