UNITED STATES DEPARTMENT OF THE INTERIOR

| FORM APPROVED | | | | | | |
|-----------------------------|--|--|--|--|--|--|
| Budget Bureau No. 1004-0135 | | | | | | |
| Expires: March 31 1993 | | | | | | |

| BUREAU OF LAND MANAGEMENT | | | | Expires: March 31, 1993 5. Lease Designation and Serial No. SF-078201 8. If Indian, Allottee or Tribe Name | |
|--|---------------------------|---|---|--|------------------------------------|
| SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals | | | | | |
| | | 50 | 3 HAY - 1 P.112 70 Palamai (G) | 7. If Unit or CA, Agreement Designation | |
| 1. Type of Weil Oil Weil Gas Weil Other 2. Mame of Operator | | Attention: | | 8. Well Name and No. Florance O | #20 |
| AMOCO PRODUCTION COMP 3. Address and Telephone No. | ANY | Gail M. Jefferso | | 9. API Well No. 3004509 | 376 |
| P.O. BOX 800 DENVER, COLO | | (303) 83 | 30-6157 ———————————————————————————————————— | 10. Field and Pool, or Exploratory Area Basin Dakota/Bland | co Mesaverde |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 990' FNL 1650' FE | Sec. 24 T | 30N R 9W | UNIT B | 11. County or Parish, State SAN JUAN | NEW MEXICO |
| 12. CHECK APPROPRIA | TE BOX(s) TO INDIC | CATE NATURE | OF NOTICE, REI | PORT, OR OTHER DA | TA |
| TYPE OF SUBMISSION | | | TYPE OF ACTION | | |
| Notice of Intent Subsequent Report Final Abandonment Notice | | Abandonment Recompletion Plugging Back Casing Repair Aftering Casing Other Plug back Dakota | | Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water | |
| 13. Describe Proposed or Completed Operations (Clearly state all permarkers and zones pertinent to this work.)* | | | d work . If well is directionally drilled, | | d and true vertical depths for all |
| Amoco Production Company per the attached procedures. | | lug back the Dakot | a horizon and retur | n the Blanco Mesaverde | to production |
| If you have any technical que concerns. | estions please contact Ma | ark Yamasaki at (30 | 03) 830-5841 or Ga | il Jefferson for any admin | istrative |
| | | | | The second secon | |
| | | | | DECEIV MAY 1 2 19 | 1977 |
| · | | | | | DIV |

04-29-1998 Sr. Admin. Staff Asst. /S/ Duane W. Spencer MAY - 7 1998



* See Instructions on Reverse Side

Florance O 20
Original Completion 6/65
TD = 7,125'
Page 2 of 2

- 1. Notify regulatory agencies (BLM, NMOCD, FIMO) 24 hours in advance of plugging activity. Contact BLM and indicate well is allotted (FIMO regulations effective April 1, 1997).
- 2. Check location for anchors. Install if necessary. Test anchors.
- 3. Have tech check for and catch plunger.
- 4. MIRUSU. Blow down well. Kill if necessary with fresh water. NDWH. NUBOP.
- 5. TOH with 1" and 2 3/8" tubing. TIH, set retainer at 6710', sting into retainer and pump 41 sacks cement across Dakota perforations. Sting out, spot 100' cement plug on retainer (12 sacks). TOH to 5925', spot cement plug from 5,925' to 5,825' (12 sacks). TOH. Test casing integrity to 500 psi. TIH with 2 3/8' tubing and land at 4,800'.
- 6. Return well to production.

Florance O 20 (DK/MV)

B24 T30N-R9W, 990 FNL, 1650 FEL API 3004509376 NM SF 078201

Proposed Plugback Wellbore Schematic

