l File



Form 9-331 Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

<u></u>
J.,

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	SF 080508A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME # 18 18 18 18 18 18 18 18 18 18 18 18 18
1. oil gas other P & A	PAF 548 - 544 9. WELL NO. 5497 - 547
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.	10. FIELD OR WILDCAT NAME 할 경험점
3. ADDRESS OF OPERATOR P O Box 208, Farmington, NM 87499	Horseshoe Gallup - そで含 11. sec., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA ###################################
AT SURFACE: 1980' FNL - 660' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE 3.8 San Juan 3.8 NM. 3.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 4 6 7 6 7 5 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	cavistrustentent albatoge final alternation of the come and the come
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* This well was plugged in the following manner: on 3-3-83s. 1. Spotted 18 sk cement plug (21.24 cu.ft.) from 2295 to 2140' 2. Found free point of casing and shot 5½" casing off-ac 2111' 3. Spotted 17 sk cement plug (20 cu.ft.) from 2140' to 2040'. 4. Spotted 30 sx cement plug (35.4 cu.ft.) from 1420-to 1315' (Note: 141s) plug is 50' below and 50' above Cliff House top. 5. Spotted 15 sk cement plug (17.7 cu.ft.) from 124 to 75'. 6. Installed dry hole marker with 10 sk cement plug. 7. Will restore location and file final notice when surface equipment is removed. *Note - left 9.2# per gal. mud between all plugs. Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED Jim L. Jacobs TITLE Geologist APPROVED BY TITLE DATE DATE DATE JUL 7-1983	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	OIL CON. DIV.