

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078207
Unit Ring

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Water Frac.	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 23, 1960


Well No. 1 is located 990 ft. from N line and 990 ft. from E line of sec. 22
N.E. Sec 22 30 N 10 W N.M.P.M.
 (34 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6327 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-21-60 Total Depth 5322. Temporary Bridge Plug at 5300. Water fractured. Fractured
 Cliffs perforated intervals: 2935-43; 2947-53; 2957-63; 2967-71, with 29,200 gallons water
 and 10,000 gal. sand. Breakdown Pressure 200 #, maximum pressure 1450 #, average treating
 pressure 800 #, 1300 #. Injection rate 31 Bbls/min. Flush 5300 gallon.
 Dropped 30 balls. 1 % Calcium Chloride 2 in Frac water. Spotted 250 gal MCA across perf.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company E. Paso Natural Gas Company
 Address Box 99
Farmington, New Mexico
 By ORIGINAL SIGNED A.M. SMITH
 Title Petroleum Engineer