

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 45-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 04443-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> Water Injection Well	7. UNIT AGREEMENT NAME O. J. Hoover "D"
2. NAME OF OPERATOR Clinton Oil Company	8. FARM OR LEASE NAME N. E. Hogback Unit
3. ADDRESS OF OPERATOR P. O. Box 2434, Casper, Wyoming 82601	9. WELL NO. 20
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL and 1980' FEL, NW NE	10. FIELD AND POOL, OR WILDCAT Horseshoe Gallup
11. SURFACE NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 24, T30N-R16W
12. ELEVATIONS (Show whether BV, TV, OR, etc.) 5379' GL	12. COUNTY OR PARISH, 13. STATE San Juan N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Squeeze perf. to 500# with 25 sks. cement.

Spot 20 sks. plug 3942'-3792'

Shoot 5 1/2" csg. @ 3000' and pull

Spot 25 sks plug 50' inside 5 1/2" csg. stub and 50' outside

Spot 50 sks. plug 2390'-2240' (Pt. Lookout 2290'-2595')

Spot 30 sks. plug 751'-675' (Menefee 725'-2290')

Spot 20 sks. plug 215'-165'

Spot 10 sks. plug 30'-G.L.

Install dry hole marker.

U. S. G. S. will be notified when location is cleaned up and ready
for final inspection.

I hereby certify that the foregoing is true and correct

SIGNED

Dean B. Bamei

TITLE Production Engineer

DATE July 30, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE