

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well GAS 2. Name of Operator BURLINGTON RESOURCES OIL & GAS COMPANY 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 816' FSL, 1130' FWL, Sec.16, T-30-N, R-10-W, NMPM, San Juan County	API # (assigned by OCD) 30-045-09434 5. Lease Number 6. State Oil&Gas Lease # B-10400-1 7. Lease Name/Unit Name Atlantic D Com E 8. Well No. 6 9. Pool Name or Wildcat Wildcat Ojo Alamo 10. Elevation:
--	--

Type of Submission	Type of Action
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Other -
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

2-5-98 MIRU. ND WH. NU BOP. TOO H w/52 jts 2 3/8" tbg & pkr. TIH w/gauge ring to 1698'. TIH w/sinker bar to 1802'. TIH w/6 1/4" mill to 1802'. SD for weekend.

2-9-98 Mill to 1807'. Circ hole clean. TOO H w/mill. SDON.


2-10-98 TIH w/6 1/4" bit to 1810'. Circ hole clean. TOO H. TIH w/6 1/2" mill. SDON.

2-11-98 Mill to 1842'. Circ hole clean. SDON. (Well plugged with old cmt retainer left from recompletion).

2-12-98 Drill cmt @ 1842-1848'. TOO H. TIH w/6 1/4" bit & csg scraper. Mill to 2804'. Circ hole clean. TOO H. TOH to PBTD @ 2859'. Perf 3 sqz holes @ 2752'. TOO H. TIH w/cmt retainer, set @ 2699'. Establish injection. Plug #1: pump 36 sx Class "B" neat cmt below cmt retainer outside csg @ 2652-2752'. Pump 19 sx Class "B" neat cmt above cmt retainer inside csg. TOO H to 1870'. Plug #2: pump 66 sx Class "B" neat cmt inside csg @ 1652-1870'. WOC. SDON.

2-13-98 TIH, tag TOC @ 1581'. PT csg to 500 psi, OK. TOO H. TIH to 310'. Perf 3 sqz holes @ 310'. Establish circ down csg & out csg valve. Plug #3: pump 75 sx Class "B" neat cmt down csg & out csg valve. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Install dry hole marker w/20 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 2-13-98.

SIGNATURE



Regulatory Administrator March 14, 1998

no

(This space for State Use)

ORIGINAL SIGNED BY E. VILLANUEVA

DEPUTY OIL & GAS INSPECTOR, DIST. #3

SEP 4 1998

Approved by

Title

Date