U. S. LAND OFFICE _Santa SERIAL NUMBER 077764

LEASE OR PERMIT TO PROSPECT -

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

Company El Pago Hatural Gas Company Address Box 990, Farmington, New Mexico Lessor or Tract Schunacher Field Basin Dakota State New Mexico Well No.12(OMO) Sec. 17 T. 30N R. 10W Meridian N.MP.M. County San Juan Location 800 ft N. of 8 Line and 800 ft E. of W Line of Section 17 Elevation Courses floor relative The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records. Signed ORIGINAL SIGNED F. S. OBERLY Title Petroleum Engineer Date March 12, 1963 The summary on this page is for the condition of the well at above date. Re-Comp. 2-14-63 Commenced drilling 5-20-, 19 62 Finished drilling 7-5-, 19 62 OIL OR GAS SANDS OR ZONES (Denote gas by G) No. 4, from _____ to ____ No. 1, from 7238 to 7382 (G) No. 2, from 7382 to 7508 (G) No. 5, from to No. 6, from _____ to ____ No. 3, from _____ to ____ IMPORTANT WATER SANDS No. 3, from _____ to ____ No. 4, from _____ to ____ CASING RECORD Kind of shoe Amount Make 204 1.55 -8-**r**d MUDDING AND CEMENTING RECORD Size casing Number sacks of cement Where set circulated 9 5/8" PLUGS AND ADAPTERS Heaving plug—Material Length Depth set Adapters—Material Size ----SHOOTING RECORD Depth shot Depth cleaned out Quantity 7-9-62: Perf 7297-7303(2 SFF);7384-88 7396-7400(3 SFF); Frac w/71,000 gallons water 80,000# send. Flush w/5000 gallons water. IR 31.5 HPM. Max pr 4300#, BDP 1350#, tr pr 3400-3200-3000#. Dropped 3 sets of 12 bells. TOOLS USED Rotary tools were used from _____ feet to _____ feet to ____ feet to ____ feet Cable tools were used from _____ feet to _____ feet, and from ____ feet to ____ feet DATES Put to producing, 19....., **....2-14**...., 19-**63** The production for the first 24 hours was barrels of fluid of which% was oil;% Gravity, °Bé. emulsion;% water; and% sediment. If gas well, cu. ft. per 24 hours 1,436,000 Gallons gasoline per 1,000 cu. ft. of gas Rock pressure, lbs. per sq. in. --1509 cesing A.O.F. 1500 MCF/D **EMPLOYEES**

		, Driller	, Driller
·		FORMATION	RECORD
FBOM-	то	TOTAL FEET	FORMATION
0 1572 1660 2580 2909 2990 4540 4722 5164 5426 6443 7178 7382 7508	1572 1660 2580 2909 2990 4540 4722 5164 5426 6443 7178 7238 7382 7508 7541	1572 88 920 329 81 1550 182 442 262 1017 735 60 144 126 33	Ojo Alamo Kirtland Fruitland Pictured Cliffs Levis Cliff House Menefee form. Point Lookout Mancos Gallup Greenhorn Graneros Dakota Morrison
	1	4	

...., Driller

.____, Driller

16-42094-3 g. s. Government Printing Office			
CONTRACTOR AND	arma i ama more	S.A. M.	
An entre of the section of the secti	e de la companya de l	terral transfer of the second	er gest de
	a serifica		
en e			
ध् • क्राक्रायुक्	NA TAL BURLE		
e e e e e e e e e e e e e e e e e e e			
en e	ene or energy es		
- 1000 (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000) (1000)			
		The extension of the second	
		• • • • • • • • • • • • • • • • • • •	The second section is a second section of the second section is a second section of the second section in the second section is a second section of the section of the second section is a section of the secti
and the second s	San		e Die Lange
- 	9 () () () () () () () () () (asett) in the	
			en (orași de la composition de
	V. 17		
	ं 8a 7 7 €.∪3	*** ** ** * * * #	A Service of the serv
	Attach.		e esta la companya de
다 보고 있는 사람들은 (現 身 기타는 사고 기타는 제) -	14 Marie 1		o Berlin
	- port particular of the state	e di i manati	enstance of a
transfer			
2000 - 12 July 19 July	5,835		
9.5F/00/27			
a satisfier in decide	95. *	~3	126334
	:		
±			
	73		
	:		
	!		
	:		
FORMATION	TOTAL FEET	—от	-MORI

	er – Grander Se. 19. Rander – Giv				
	The Constant of the Section of the S	D LAG SO C.			4450 n. an .
			!		<u></u>
$\mathbf{x}^{(i)} = \mathbf{x}^{(i)} \cdot \mathbf{x}^{(i)} = x$	may a well				
and the second					
	WAITED DANES				
en a company of the second second	So C Res		1. 10	* * * * * * * * * * * * * * * * * * * *	and a second
the second of th	$w_{x} \mapsto w_{x}$				in the same of
a territoria	758 0 387	A Commence			
State August Teacher	FREE STATES CONTRACTOR	Gt Burn desire	ile sh	শ্বর্থ হয় ক্রেন্ট্র রেশ্যা	The second of th

LANGE OF LINE OF THE SECTION

the second state of the second

ANV SANCE NO 90 POR

PRODUCT CONSTRUCTION POPULATION OF THE CANADA Theres in the company

and all the second

and the state of the same of t

and also been selected as early stage. and **times.£** for a joing to the color

Paul ... - Com. . - .

Show details of tubular goods, bottom hole accessories, DST's, Cores, Deviations, and General Chronological History).

5 -2 0-62	Brannon & Murray spud well.
5-21-62	Ran 9 jts 9 5/8" 36# J-55 casing (284') set @ 301' w/200 sacks regular, 1/4 cu ft. Strata-Crete"6"/sk.
5-22-62	Drilling.
5-30-62	Lost circulation 18 1/2 hours. Lost 72 jts. 4 1/2" drill pipe & 25 collars
	in hole.
5-31-62	K Fishing.
6-1-62	Fishing.
6-2-62	Milling on fish, have hold of fish, unable to pull, ran free point by Dia-lgg.
6-3 -62	Recovered 72 jts. drill pipe. Left 25 collars w/tool joint on top. CO Top of fish @ 4686'.
6- 5-62	Recovered 9 drill collars. 16 still in hole.
6-7-62	Spotted 250 sacks cement plug from 4350-5050'.
6-9-62	Cementary too soft to whipstock. Spotted 250 gal 73% MCA & 65 sacks El Toro "35", 2% calcium chloride, 20-40 sand, from 4470-4690'.
6-12-62	Spotted 100 sacks cement 15# 20-40 sand. 45# Activated charcoal/sk.,
0-12-02	2% HA-5 (4400-4720). Bradenhead squeezed to 200 psi for 1 hrs
6-13-62	Top of cement @ 4515'.
6-14-62	Cement too soft to whipstock.
0-14-02	Spotted 75 sks regular cement, 15% 20-40 sand, 3% HA-5 4700-4500'.
6-17- 62	Set Whipstock.
6-18-62	Drilling.
6-22-62	Lost circulation 4 hrs.
7-2-62	Lost 3 cones in hole. Recovered fish.
7-3-62	Drilling.
7-5-62	Reached T.D. Ran IES & GG log.
7-7-62	Ran 236 jts. 4 1/2" casing (32 jts. 11.6#, 197 jts. 10.5#, 7 jts. 11.6#)
1 1 50	for a total (7529') set at 7541'. Cmted 1st stage w/80 sacks regular, 4%
	gel, 1/4# tuffplug/sk., 1/8# flocele/sk., 0.4% HR-4 & 50 sacks regular,
	1/4# tuffplug, 0.4% HR-4. 2nd stage w/260 sacks El Toro"35", 4% gel,
	1/4 cu. ft. Strata-Crete"6"/sk. 3rd stage w/325 sacks El Toro"355", 66 gel.
7-9-62	Perf 7297-7303; (2 SPF); 7384-88;7396-7400 (3 SPF); Frac w/7100 gallons
, ,	water, 80,000# sand. Flush w/5000 gallons water. I.R. 31.5 BPM. Max pr
	4300#, BDP 1350#, tr pr 3400-3200-3000#. 3 drops of 12 balls.
7-10-62	Blowing well.
7-12-62	Ran 238 jts. 2 3/8"4.7#, J-55 tubing (7397') set at 7408'.
	Shut in for test.
7-19-62	Date well was tested.
	WORKOVER
1-16-63	Moved S. S. Reames on location to workover.
1-17-63	Set Choke @ 7400'. Pulled tubing. Gas blowing around backside of 9 5/8" casing.
0 (0	Tried to run junk basket. Stopped @ 1074'.
1-18-63	Killed well w/mud. 4 1/2" csg. was parted @ 1074, pulled 1074' of 4 1/2" casing.
1-19-63	Washed over 4 1/2"csg. to 1098'. Re-ran top part of 4 1/2" csg. & tied together
1 00 62	w/Bowen csg. bowl. Set slips w/25,000#. Casing patch @ 1077'.
1-20-63	Set full bore pkr @ 1805' & tested casing to 2500#. Cemented backside of 4 1/2"
1 01 62	casing w/150 sks. regular cement. Came out of hole w/packer.
1-21-63 2-14-63	Re-ran 237 joints 2 3/8" tubing. 7360' landed @ 7370'. Shut well in for test. Date well was tested.
∠ -14-02	Daug well was desied.