


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. NM-09867-A

~~XXX~~ Lunt Lease



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

RECEIVED
MAY 21 1962
U.S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 21, 1962, 19

Well No. 66 is located 1690 ft. from N line and 990 ft. from E line of sec. 17

Sec. 17 30 N 12 W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Basin Dakota Santa Fe New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5600 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Drilled 12-3/4" surface hole, set 8-5/8" casing to 235' and circulated cement. Mud drilled 7-7/8" hole to 6250'. Set 4-1/2" x 11.60# production casing to TD and cemented with 300 sacks - 100 sacks thru shoe (Dakota), 100 thru PV tool at 5495 (Gallup) and 100 at 6250 (Mesa Verde). Perforated Dakota and sand-water fraced - 4 stages. Landed 2-3/8" tubing at 6155'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company B & G Drilling Company, Inc.

P. O. Box 327
Address Farmington, N. M.

By _____

Title William C. Russell
President