NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS Revised 12-1-55

.ooT	Basin Dal	ota		Fo	rmation	Dak	pta		County	San J	iar
niti	ial X		_Annual	· <u></u>		Sp ec	ial		Date of	Test 🍮	stember 20, 1
ompa	any Pan Am	ricen	Petro la	een Co	ro	Lease_ Jo	hracen Ga	s Undt "	שר Wel	l No	1
nit	_ 	Sec	Twp.	30	Rg Rg	≅. <u>12</u> √	Purc	haser			
asir	ng <u>(-1/2"</u> W		.5# .6#_I.□			t at_ 666	1 Pe	rf. 651	7•	To 65	271
						-					
											ess. 12
	cing Thru:							_			
							Sin	gle-Brad	enhead-G.	G. or (G.O. Dual
200	or complete	1011	Am I Amil I	· · · · · ·	acker			RESET V	oll temb.	M43" F	
	1 (7)	(=	\ (a)		(25 · · · · · · · · · · · · · · · · · · ·		ED DATA				
	d Through								Type Tap		•
7	(Prover)		Low Dat		Diff.	Temp.	Tubing Press.		Casing D	Temp.	Duratio
·-	(Line) Size		ice) ze	psig	h _w	o _F .	psi <i>g</i>	o _F ,	psig	o _F	of Flo
	Shut-in	7 4	AYS		W		1966	<u> </u>	1964		
	2 in.	3/4	in.	201			250	SC"(det.)	526	60°es	3 102.
$oldsymbol{\perp}$											
<u>+</u>											
 -							CULATION	CHARLES THE PARTY NAMED IN COLUMN 2 IN COLUMN 2			
			_	Fa		Temp. Gravity ctor Factor		Factor		Rate of Flow Q-MCFPD	
\downarrow			√ h _w p _f	w ^p f psia					F _{pv}		0 15.025 psia
上	12.365					1,000		.9258	Astx	,	
											
					PRE	SSURE CA	alcuiati	ONS			
	quid Hydro					cf/bbl.					rator Gas
	y or Liqui		(1-	e <mark>-s</mark>		deg.		P _{c_19}	76	P _c 3.9	ring Fluid
	D .	P _t 2	F _C Q		$(F_cQ)^2$	(F.	م _ا 2	P _w 2	P _c -P _w ²	Ca	ıl. P.
	$P_{\mathbf{w}}$	F.L	- C	İ	(-64)	(1	.Q) ² -e−s)	- W	- G - W	F	Pw Pc
	P _w	rt						10 7 70 A	6 / 18 242		
]		rt						87,296	3,617,280		
]		t-						296	3,617,250		
,		-ft						27,296	3,617,280		
solu	Pt (psia) ute Potent	ial:	Petrole	reas Co	rporeti	MCFPD;			3,617,280	OF	TIVED
solu MPAN DRES	Pt (psia) ute Potent NY Pan Am SS Pag 48	ial:	introl	Hew Mew	l'exten	_MCFPD;	n	,75		RE	FIVED 1961
solu MPAN DRES	Pt (psia) ute Potent NY Pan Am SS Bar Ad and TITLE SSED	ial:	introl	Hew Mew	l'exten	_MCFPD;	n	,75	3,517,200	RE	13 1961 CON. COM.

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 600 F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{W}}^{\perp}$ Differential meter pressure, inches water.
- F_{g} Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n _ Slope of back pressure curve.
- Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.