


U. S. LAND OFFICE Santa Fe  
SERIAL NUMBER 080508  
LEASE OR PERMIT TO PROSPECT Harrington



# LOG OF OIL OR GAS WELL

### LOCATE WELL CORRECTLY

Company BENSON-MONTIN-GREER DRILLING Address 150 Petroleum Center Building  
CORP. Farmington, New Mexico  
 Lessor or Tract Harrington Field Undesignated; State New Mexico  
 Well No. 1 Sec. 17 T. 30N R. 15W Meridian N.M.P.M. County San Juan  
 Location 1980 ft. [N] of N Line and 530 ft. [E] of W Line of Sec. 17 Elevation 5378  
[S] [W] (Depth, floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed Stanley

Date December 4, 1961 Title Engineer

The summary on this page is for the condition of the well at above date.

Commenced drilling August 31-----, 1961 Finished drilling November 3 ; -----, 1961

## OIL OR GAS SANDS OR ZONES

(Denote gas by  $G$ )

No. 1, from 4130½ to 4140½ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

No. 2, from \_\_\_\_\_ to \_\_\_\_\_      No. 5, from \_\_\_\_\_ to \_\_\_\_\_

No. 3, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

No. 1, from \_\_\_\_\_ to \_\_\_\_\_

No. 2, from \_\_\_\_\_ to \_\_\_\_\_

## CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	20#	8	J-55	4270	Texas	4180	4140	Surface	
4-1/2"	10.5#	8	J-55	4270	Pattern			Production	
								Tubing	
2-3/8"	4.7#	EUE		4121	-	-	-	String	

## MUDDING AND CEMENTING RECORD

	Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
MARK	8-5/8"	100	90	Pump & Plug		
	4-1/2"	4269.5	175	" "		

## PLUGS AND ADAPTERS

Heaving plug—Material None Length \_\_\_\_\_ Depth set \_\_\_\_\_

Adapters—Material None Size           

## SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out
		None				

## TOOLS USED

Rotary tools were used from 103 feet to 4270 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet.

Cable tools were used from Surface feet to 103 feet, and ~~from~~ to complete feet to \_\_\_\_\_ feet

## DATES

[illegible]

Put to producing ----- **December 1** -----, 19--**61**

The production for the first 24 hours was 91.2 barrels of fluid of which 100% was oil; -----% emulsion; -----% water; and -----% sediment. Gravity, °Bé. 42-----

If gas well, cu. ft. per 24 hours ----- Gallons gasoline per 1,000 cu. ft. of gas -----

Rock pressure, lbs. per sq. in. \_\_\_\_\_

## EMPLOYEES

Stone Drilling Company, Driller \_\_\_\_\_, Driller

\_\_\_\_\_, Driller

## FORMATION RECORD

FROM--	TO--	TOTAL FEET	FORMATION
			<u>ELECTRIC LOG TOPS</u>
			Start in Pictured Cliffs.
			Top Lewis 115'
			Top Mesa Verde 965'
			Top Menefee 1590'
			Top Point Lookout 2745'
			Top Mancos 2800'
			Top Gallup ; 3790'
			Base Gallup 4142'
			Top Sanastee 4233'
FROM--	TO--	TOTAL FEET	FORMATION