

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division

Sundry Notices and Reports on Wells

|   |   |
|---|---|
| <p>1. <b>Type of Well</b><br/>GAS</p> <hr/> <p>2. <b>Name of Operator</b><br/><b>BURLINGTON</b><br/><b>RESOURCES</b> OIL &amp; GAS COMPANY</p> <hr/> <p>3. <b>Address &amp; Phone No. of Operator</b><br/>PO Box 4289, Farmington, NM 87499 (505) 326-9700</p> <hr/> <p>4. <b>Location of Well, Footage, Sec., T, R, M</b><br/>1020' FNL, 1030' FEL, Sec. 14, T-30-N, R-11-W, NMPM, San Juan County</p> | <p>API # (assigned by OCD)<br/>30-045-09532</p> <p>5. <b>Lease Number</b><br/>Fee</p> <p>6. <b>State Oil&amp;Gas Lease #</b></p> <p>7. <b>Lease Name/Unit Name</b><br/>Hampton SRC</p> <p>8. <b>Well No.</b><br/>3</p> <p>9. <b>Pool Name or Wildcat</b><br/>Aztec Pictured Cliffs</p> <p>10. <b>Elevation:</b></p> |
|---|---|

| Type of Submission                                    | Type of Action                                   |
|---|--|
| <input type="checkbox"/> Notice of Intent             | <input checked="" type="checkbox"/> Abandonment  |
| <input checked="" type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion            |
| <input type="checkbox"/> Final Abandonment            | <input type="checkbox"/> Plugging Back           |
|   | <input type="checkbox"/> Casing Repair           |
|   | <input type="checkbox"/> Altering Casing         |
|   | <input type="checkbox"/> Other -                 |
|   | <input type="checkbox"/> Change of Plans         |
|   | <input type="checkbox"/> New Construction        |
|   | <input type="checkbox"/> Non-Routine Fracturing  |
|   | <input type="checkbox"/> Water Shut off          |
|   | <input type="checkbox"/> Conversion to Injection |


13. **Describe Proposed or Completed Operations**

2-3-98 MIRU. ND WH. NU BOP. TOO H w/111 jts 1" tbg. TIH w/5 1/2" gauge ring to 2400'. TIH w/5 1/2" CIBP, set @ 2364'. TOO H. Load hole w/54 bbl wtr. PT csg & CIBP to 500 psi, OK. Plug #1: pump 50 sx Class "B" neat cmt @ 1924-2364'. TOO H. TIH, perf 3 sqz holes @ 1200'. Establish injection. TIH w/cmt retainer, set @ 1140'. Plug #2: pump 79 sx Class "B" neat cmt below cmt retainer outside csg. Pump 24 sx Class "B" neat cmt above cmt retainer inside csg @ 979-1200'. TOO H. SDON.

2-4-98 TIH, perf 3 sqz holes @ 150'. Establish circ down csg & out bradenhead. Plug #3: pump 75 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Fill csg & install dry hole marker w/15 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 2-4-98.

**RECEIVED**  
FEB 12 1998

**OIL CON. DIV.**  
DIST. 3

SIGNATURE  Regulatory Administrator February 10, 1998

(This space for State Use)

Approved by ORIGINAL SIGNED BY E. VILLANUEVA Title DEPUTY OIL & GAS INSPECTOR, DIST. 3 Date SEP 9 1998