## NEW MEXICO OIL CONSERVATION COMMISSION

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

			ii DE	PORT ON REF	ATRING W	ZET T.	11
REPORT ON OPERAT	BEGINNING DRILLI IONS	ING	X				
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL			RE	REPORT ON PULLING OR OTHERWISE ALTERING CASING			
	RESULT OF TEST O		I RE	PORT ON DEE	PENING V	VELL	
REPORT ON	RESULT OF PLUGGI	ING OF WELL					
		Anril	14, 1951	Fai	rmington	. New 1	Mexico
		(A grade de de	Date	***************************************			Place
			. Litain ad an dan th	a haading noted	ahove at th	۵	
	report on the work do	ne and the results o	State	e neading noted	above at th	XIX	3 : +1
	Company or Ope	rator	Lea	ase	Well No		In u
ratar 1/4		of Sec.	, T	30	, R	9	, N. M. P. M
Notice of inte		(was not) subm (was not) obtain D ACCOUNT OF	uitted on Form C- led. (Cross out inc WORK DONE A	102 onorrect words.)	OBTAINE	D	19
Notice of inte and approval ell was spu 9.50# SS Su o surface. ith no drop easured for 10' as of 7 ell will be	ntion to do the work <b>X</b> of the proposed plan	(was not) subm (was not) obtain D ACCOUNT OF Y 11/51 and dri nded at 273' ng plug out of g out cement se; fluid lev ffhouse Sand on. At T.D. I	work done a dilled to T.D (KB) with 2 casing was trotary was and set 7 <sup>th</sup> Rotary will	orrect words.) ND RESULTS of 375. OO sacks of steel with stopped and stationar, casing, robe replace	OBTAINE  Ran 6 of regular  500# prod fluid  y. Well  tary will  d with	of the of the construction	10-3/4*426 nt and circ for 30 Mir in casing to drilling a drill thro cols for co
Notice of inte and approval ell was spu 9.50# SS Su o surface. ith no drop easured for 10' as of 7 ell will be esa Verde f etion, well	ntion to do the work to f the proposed planks DETAILE.  dded 2:30 PM 4/rface casing la Prior to drilling after drilling any drop or rison any drop or rison and 4/14/51. drilled to Cli or gas completically will then be seen and the seen and	(was not) subm M(was not) obtain D ACCOUNT OF Y 11/51 and dri nded at 273' ng plug out of g out cement se; fluid lev ffhouse Sand on. At T.D. I hot with Nith	work done a liled to T.D (KB) with 2 retary was wel remained and set 7" Rotary will ro in the Po	orrect words.) ND RESULTS of 375. OO sacks of steel with stopped and stationar, casing, robe replace	Ran 6 of regals 500% produced fluid with tary will tary	ts. of ar ceneressure level: is now then Cable Tossibly	10-3/4*426 nt and circ for 30 Mir in casing w drilling a drill thru cols for co the Cliff

1951

Company or Operator

Address 305 W. Mein St. - Farmington, N.M.

April 20,

Date