

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports 66 SEP 19 11 2:17

RECEIVED
SEP 16 1996

070 FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
990' FNL, 990' FWL, Sec. 17, T-30-N, R-10-W, NMPM

D

5. Lease Number
SF-077764
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Schumacher #5
9. API Well No.
30-045-09552
10. Field and Pool
Aztec Pictured Cliffs
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

- | | | |
|---|---|--|
| ☐ Notice of Intent | ☒ Abandonment | ☐ Change of Plans |
| ☒ Subsequent Report | ☐ Recompletion | ☐ New Construction |
| ☐ Final Abandonment | ☐ Plugging Back | ☐ Non-Routine Fracturing |
| | ☐ Casing Repair | ☐ Water Shut off |
| | ☐ Altering Casing | ☐ Conversion to Injection |
| | ☐ Other - | |

13. Describe Proposed or Completed Operations

8-26-96 MIRU. ND WH. NU BOP. SDON.

8-27-96 TOO H w/145 jts 1" tbg. TIH w/5 1/2" gauge ring to 2925'. TOO H. TIH w/5 1/2" BP, set @ 2900'. TOO H. TIH, load hole & circ hole clean w/63 bbl wtr. PT csg to 500 psi/5 min, OK. Plug #1: pump 12 sx Class "B" cmt @ 2794-2900'. TOO H to 2646'. Plug #2: pump 18 sx Class "B" cmt inside csg @ 2487-2646'. TOO H to 1704'. SDON.

8-28-96 TIH, perf 3 sqz holes @ 1760'. TOO H. Establish injection. TIH w/5 1/2" cmt retainer, set @ 1704'. Establish injection. Plug #3: pump 68 sx Class "B" cmt outside csg below cmt retainer @ 1552-1760'. Pump 23 sx Class "B" cmt on top of cmt retainer, TOC @ 1501'. TOO H. TIH, perf 2 sqz holes @ 159'. TOO H. Pump 90 bbl wtr down csg. Pump 40 bbl wtr down bradenhead. Well would not circ. (Verbal approval to change plans from Joe Sanchez, BLM). Perf 2 sqz holes @ 119'. Establish circ down csg & out bradenhead w/3 bbl wtr. Plug #4: pump 75 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Fill 5 1/2" csg w/2 sx Class "B" cmt. Install dry hole marker w/1 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 8-28-96.

14. I hereby certify that the foregoing is true and correct.

Signed Duane W. Spencer Title Regulatory Administrator Date 9/5/96

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

A P E D
SEP 2 1996
/S/ Duane W. Spencer

MMOCD