## Revised 12-1-55

# MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool	ol Besia Bebets			Formation Babeta				County		Sen Juan	
Init	ial		Annual_		Spec:	ial		_Date of T	'est	9-9-64	
										1	
Unit	Se	ec. 👪	Twp.	Rg	e. <b>13</b> 0	Purcl	haser				
Casi	ng 4-1/2 Wi	. <b>10.</b> 5	I.D.	<b>.052</b> Se	t at <b>63</b>	Per	rf	3-40 1-4402	0	15-23 18-44	
Tubi	ng <b>2-3/8</b> Wi	t. <u>4.1</u>	i.D <u>_</u>	<b>.993</b> Se	t at <u>63</u>	A2 Per	rf	6305	ro	6911	
Gas !	Pay: From_	6332	To <b>6443</b>	L	300 x	G .700		4473 E	Bar.Pres	s. <u>12</u>	
Prod	ucing Thru:	Casi	ng	Tu	bing	Sin	Type We gle-Brade	11 st	or G.	O. Dual	
					OBSERV.	ED DATA					
Test	ed Through	<u>(</u>	(Choke	e) <b>(****</b> )				Туре Тар	. The		
	<u></u>	F1	ow Data			Tubing	Data	Casing Da	ta		
No.		(Chok	e) Pres	ss. Diff.		Press.	Temp.	Press.	Тетр.	Duration of Flow	
	Size Si		e ps	ig h <sub>w</sub>	o <sub>F</sub> .				°F.	Hr.	
	9 Days 2 Inch	. 745				3012	se oot.	1007 696		. 3 %.	
2.	- Auge	.,,,,		<u>'</u>							
3.											
4.											
No. Coefficient Pressure Flow Temp. Gravity Compress. Factor Factor Factor Factor Fpw $f_{\rm py}$ Psia Ft Fg $f_{\rm py}$								r	Q-MCFPD		
			V <sup>n</sup> w <sup>p</sup> f			t	.9256 1.43		3716		
1.	13.3639			313	1.000		+7639	1.637		3/49	
2 <b>.</b> 3.											
4.					···						
5.										·	
	iquid Hydro				cf/bbl.		Speci	fic Gravi	ty Sepai	rator Gas_	
Gravi Fc	ty of Liqui	а нуаго	carbons(1-e-	s)	deg.	- -	P <sub>c</sub>	3039	P <sub>C</sub>	ing Fluid	
No.	P <sub>w</sub>	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	) (F	(cQ) <sup>2</sup> (-e <sup>-s</sup> )	P <sub>w</sub> 2	$P_c^2 - P_w^2$	Ca.		
1.	- 0 (P)					<b>X</b>	N, 100	3,633,421			
1. 2. 3.						T	· · · · · · · · · · · · · · · · · · ·		-		
3.		<del>-</del>	+	+		<del></del>		<del> </del>	AND SECTION AND SE		
4.										William	
Absolute Porential: MCFPD; n									SEP	25,00	
ADDRES									E THE LAND	- 136A	
A COTOR			_	Blatylat	- Bankson		<del></del>		1 : 6	<del>)                                    </del>	
	T and TITLE	By:	ORIGINAL SI	GNED BY	- Inglass				1 Dia	T. SCM.	
WITN		By:	ORIGINAL SI	<b>District</b> GNED BY Deli	Bagtaon				Die	25 1964 1. SCM.	

## KIRD SILDISADD

#### INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

### NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- $P_c$  72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{w}$  cannot be taken because of manner of completion or condition of well, then  $P_{w}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{+}$ .