## MULTI-POINT BACK PRESSURY TEST FOR GAS WELLS Revised 12-1-55

Pool	Undes1	gnate	od		_Format	tion	Dakot	ia money sugar	and the state of t	County	San	Juai	1
	ial XX												
	any R&G												
	NE/NE											KW ( )- app ( - compress, c - compress, c	
	ng <b>b}</b>											6166	
	ng <b>2*</b> W												
	Pay: From												12.0
											_	_	
Date	ucing Thru: of Complet	ion:	R_26.		Da	ruc	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	3	ingle-Bra	denhead-G	G. or	G.O.	Dual
5400	Or Complet	1011	9-20	-44	ra	cxei				voir lemp	·		
M 4	l mi	/ mattered season	******* /				OBSERV	ED DAI	<b>Á</b>				
Test	ed Through					et.					lps		
$\neg$	(Prover)	(Che	Flow Doke)	Dno	cc D:	ff.	Temp.	Tub Pre:	ng Data s. Temp	Casing Press.	Data Temo.	-	Duration
No.	(Line) Size	(Orid	fice)	ps	ig h	ا	o <sub>F</sub> .	ř	g op.				of Flow
SI		3/4	n	<u> </u>		*		1738	C. Learning Co.	1972			112 3
1. 2. 3.								интерритического населения у <sub>ставо</sub>		1210			
<u>3.  </u> 4.								302	80	10/0		3 7	ours
4. 5.					The second second			<b>Sample parts</b> (Sample Same)				1	
			r	·,	- Control of the Control		LOW CAL			N. Colle To I.T. At ago: an and the agreement of the agre			
No.	(24-Hour)				i		Da	Flow Temp. Factor			ess. or	Rate of Flow	
$\downarrow$			√ h <sub>w</sub> l	o <sub>f</sub>	psia		F.	j	1.0	Fpv	Fpv		● 15.025 psia
1. 2. 3. 4.					314	214		.9813		1.0	28	3917.5	
3。 4.						$\Box$		Townships to a					
5.								and the second	C. International Contractions				
						PRE	SSURE CA	ALGULAT	TIONS				
as Li	quid Hydro	arbon	Ratio	)		'1	cf/bbl.		Spec	oific Grav	ity Sen	arato	r Gas
ravit c	ravity of Liquid Hydrocarbons deg								Specific Gravity Flowing Fluid Pc 1984 Pc 3936.25				Fluid
c				L <del>-e</del> -	1	···	<del></del>		Y Com-	TÀOA	Pc	147e	·47
T	$P_{\mathbf{w}}$		1					The second of th	· ATTITION OF THE PROPERTY OF	2 0			
No.	Pt (psia)	Pt	F	Q	(F <sub>c</sub>	(2) <sup>2</sup>	(*	-e-s)	$P_{_{\mathcal{W}}}2$	$P_c^2 - P_w^2$	Ca	al.	$\frac{P_{\mathbf{w}}}{P_{\mathbf{c}}}$
2.						····			1170.72	2765.	53	W	.545
3.		<del></del>	_		_								
4. 5.													
· ·	ute Potenti	al:	5.10	<b>A</b>	<u> </u>		MCFPD;	7	5	)			
COMPA ADDRE	NYR	40	DELL	ing	Comps	ny				emikist og men misken. Skimit i s	mananti katamitatuna 1812 aug		
	and TITLE	BÜ	1 R.	Bas	tings,	TITLE STATE	ton, H	tativ	rigo B	water was a state of Salar a delicant from Salar and		110	
	SSED_							ner alle de la company de la c		e e amone summero que en en enero en encomentario	7071.		
OOMFA	TA T		·				REMA	IRKS			1777	010	61
											SEP?	Land C	;o**•∮
										*	\ mit_S		

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P<sub>W</sub>). MCF/da. @ 15.025 psia and 60° F.
- $P_c$ = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{W}}\mbox{\fontfame}$  Differential meter pressure, inches water.
- Fg Gravity correction factor.
- $F_t$  Flowing temperature correction factor.
- $F_{pv}$  Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\rm W}$  cannot be taken because of manner of completion or condition of well, then  $P_{\rm W}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\rm t}$ .