UNITED STATES DEPARTMENT OF THE INTERIOR Verse side) GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE. (Other instructions on

Form approved. Budget Bureau No. 42/R1424. 5. LEASE DESIGNATION AND SERVAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SF 081299-A

| SUNDRY | NOTICES | AND | REPORTS | ON | WFIIS |
|---------|-----------|--------------|----------------|--------------|-------|
| 3011011 | 1 10 1165 | / \l \ \ \ \ | MEI OIVIO | \mathbf{v} | ** |

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.) 7. UNIT AGREEMENT NAME GAS WELL X OTHER 2. NAME OF OPERATOR Clinton Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 2434

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)

At surface

770' FNL and 650' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 5549'

J. J. Lommori "A" 8. FARM OR LEASE NAME

NE Hogback Unit

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT Horseshoe Gallup

11. SEC., T., R., M., OR BLK. AND

-T30N-R16W 12. COUNTY OR PARISH 13. STATE

San Juan N. Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING ABANDON MENT® REPAIR WELL CHANGE PLANS (Norm: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Casing: 8-5/8" - set at 214' w/160 sacks cement

5-1/2" - set at 3180' w/80 sacks cement w/6% gel and 50 sacks cement

Perf:

3006'-3036' Upper Gallup

3100' - 3122' Lower Gallup

Propose to place sand bridge from PBTD - 3143'-2970'

Place 15 sack cement plug from 2970'-2850'

Shoot off 5-1/2" casing, Pull and lay down.

Place cement plug 50' inside 5-1/2" casing stub and 50' above casing stub

Place 50 sack cement plug from 1350'-1500' (Pt. Lookout 1461'-1675')

Place 20 sack cement plug from 214'-164'

Place 10 sack cement plug from 30' - GL

Install dry hole marker

Clean up location

| 18. I hereby certify that the foregoing is true and correct SIGNED | TITLE Roby MAN D'S | + Margon DATE |
|--|--------------------|---------------|
| (This space for Federal or State office use) | | |
| APPROVED BY CONDITIONS OF APPROVAL, IF ANY: | TITLE | DATE |