

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from -0- feet to 1351' feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19.
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Devonian	T. Ojo Alamo	
T. Salt	T. Silurian	T. Kirtland-Fruitland	
B. Salt	T. Montoya	T. Farmington	
T. Yates	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta	T.	T. Morrison	
T. Drinkard	T.	T. Penn	
T. Tubbs	T.	T. Gallup 1130'	
T. Abo	T.	T.	
T. Penn	T.	T.	
T. Miss	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
-0-	70	70	Sand & Shale	OIL CONSERVATION COMM AZTEC DISTRICT OFFIC. COPIES RECEIVED 6			
70	1082	1012	Shale	NO FURNISHED			
1082	1130	48	Core #1	1			
1130	1182	52	Core #2	1			
1182	1245	63	Shale	1			
1245	1297	52	Core #3	2			
1297	1351	54	Shale	1			
		1351	Total Depth				
Ran Schlumberger ES Induction Log Obtained verbal approval to plug well. Set cement plug from 1150' to 1100' with 15 sacks. Set cement plug in surface casing with 5 sacks. Completed plugging operations at 10:30 PM 1-11-58. Pits have been filled and the location levelled.							

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

January 30, 1958
Company or Operator Ken Blackford Address Box 1527, Farmington, New Mexico
Name Ken Blackford Position or Title Operator

Santa Fe, New Mexico

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Ken Blackford

State of New Mexico (E-9991)

(Company or Operator)

(L229)

Well No. 1-16, in NW ¼ of NE ¼, of Sec. 16, T. 30 N, R. 16 W, NMPM.

Horseshoe Canyon

...Pool,

San Juan

County.

Well is 330 feet from North line and 2310 feet from East line

of Section 16 If State Land the Oil and Gas Lease No. is E-9991

Drilling Commenced 1-2-58, 19..... Drilling was Completed 1-11-58 19.....

Name of Drilling Contractor..... **Benson-Montin-Greer Drilling Corp.**

Address.....Farmington, New Mexico

Elevation above sea level at Top of Tubing Head.....5284 GL..... The information given is to be kept confidential until
..... 19.....

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from to feet.

No. 4, from to feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24#	New	61.70'	Texas Pattern			Surface casing

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/4"	8 5/8	63' GL	50	Pump		
7 7/8	---	1150'-1100'	15	Pump		
12 1/4"	8 5/8	In surface	5			

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation.....

..Depth Cleaned Out.....

