

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FSL & 1650' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) _____

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
JAN 14 1983

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Report results of multiple completion or zone change on Form 9-330.)

OCD Received
2-16-96
D:ST 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-4-83 Unable to pull tubing free, established circulation. Tubing parted at tubing hanger. Recovered 100 joints of tubing with overshot. Left five joints tubing in hole with top of fish at 2518'. Received verbal approval from H.P. Walters this date to modify procedures.
1-5-83 Set packer at 2508'. Established rate of 2 BPM, at 250 psi. Pulled out of hole. Set cement retainer at 2508'. Squeezed Pictured Cliffs perfs with 25 sacks Class "B" cement. Tripped out of hole with 2-3/8" tubing.
1-6-83 Found freepoint of 4-1/2" casing at 2270'. Shot casing off at 2250'.
1-7-83 Pulled 69 joints (2250') of 4-1/2" casing. Spotted 50 sacks cement plug from 2290' to 2090'. Spot 50 sacks cement plug from 1350' to 1100'. Spotted 25 sacks cement from 150' to 50'. Cut off wellhead & install dry hole marker w/ 5 sacks Class "B" cement.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Engineer DATE January 11, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY

FARMINGTON

*See Instructions on Reverse Side
FARMINGTON COPY

Operator

APPROVED

JUL 30 1984
M. MILLENBACH
AREA MANAGER