STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10:01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

								Well		
Operator	MERIDIAN OIL INC.			Lease	SAN JUAN			No.	10	
Location of Well:	Unit M Sec	t 10 Twp.	30N	D.co	10W	Cuen		CAM IIIAA	1	
or well.	Unit M Sect 10 Twp. 30N NAME OF RESERVOIR OR POOL				Rge. 10W TYPE OF PROD.		METHOD OF PROD.		PROD. MEDIUM	
	TABLE OF RESERVOIR OR TOOL				(Oil or Gas)		(Flow or Art. Lift)		Tbg. or Ceg.)	
Upper				 				1001	<u> </u>	
Completion	PICTURED CLIFFS		GAS FLOW		FLOW	TBG				
Lower										
Completion	MESAVERDE				GAS	İ	FLOW	TT	BG	
		PRE-	FLOW SHUT	-IN PRE	SSURE DATA					
Upper	Hour, date shut-in	Length of time shut-in		SI press	SI press. psig		Stabilized? (Ye			
Completion	6-2-95	7 DAY	'S	ļ	196					
Lower						į				
Completion	6-2-95	5 DAY	rs	_1	303	3				
		- - :	FLOW TEST	NO. I	1					
	T	-95			Zone producing	T -	Lower)	LOWER		
TIME	LAPSED TIME	PRES			PROD. ZONE					
(hour,date)	SINCE*	Upper Completion	Lower Comp	letion	TEMP	├	REMAR	KS		
5.Jun		191	30	:1						
		1		•		<u> </u>				
6-Jun		195	30	2						
				_						
7-Jun		196	30	3	 	╁				
8-Jun		199	25	52						
						 				
9 Jun		201	30)4		<u> </u>				
Production	rate during test		1		<u> </u>					
Oil:	BOPD based on	Bbls.	in	Hours	·	Grav.		GOR _		
Gas:		MCFPD; Tested th	ru (Orifice or	Meter):						
	<u> </u>	1		-IN PRE	SSURE DATA	<u> </u>				
Upper	Hour, date shut-in	Length of time shut-in	1	SI pres. psig			Stabilized? (Yes or No)			
Completion		-		- 						
Lower	Hour, date shut-in	Length of time shut-ir	1	SI pres	s. psig		Stabilized? (Ye	s or No)		
Completion		ı					1			

FLOW TEST NO 2

Commenced:	it hour,date)**		_	Zone producing (Up)	per or Lower):		
ПМЕ	LAPSED TIME	PRESSURE		PROD. ZONE			
-hour.date)	SINCE**	Upper Completion	Lower Completion	TEMP.		REMARKS	
						·	
· . <u>-</u>	-						
	 						
			 				
							
Production	rate during test						
O.1							
Oil:	BOPD based on		_ Bbls. in	Hours.	Grav.	GOR	
Gas:		MCFPD: Te	sted thru (Orifice or	Meteri:		<u>-</u>	
Remarks:							
	-			····			
I hereby cer	tify that the informa	ation herein containe	d is true and complet	te to the best of my ki	nowledge.		
							
Approved	John	y Robinson	S 9	Operator	Meridian C	Dil Inc.	
	"	9	7				
New Mex	w Mexico Oil Conservation Division			Ву	Tanya Atcitty		
	1 10	L 1 9 1995	1				
By			L. I	Title	Operations	s Associate	
	DEPUTY O	IL & GAS INSPECT	TOR!				
Title	52.0110	iz a ano mor co	<u> </u>	Date	7/12/95		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- :. A pacter reassage test shall be commenced on each multiply commeted well within seven days after except that the previously produced zone shall remain sout-in while the zone which actual completion of the well, and annually thereafter as prescribed by the order authorizing the mutiple completion. Such tests shall also be connected on all multiple completions within seven days following recompletion and/or chemical or frac-ture treatment, and whenever remedial work has been done on a wet, during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators small also be so
- 3. The nacker leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization, both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days,
- 4. For flow Test No. 1, one zone of the dual completion small be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days if the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a cas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall he three hours.
- 5. Following completion of flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1

- was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen minute intervals during the first hour thereof, and at hoursy intervals thereafter, including one pressure measurement immediately prior to the flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gaz zone.
- 8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division of Northwest New Mexico Packet Leakage Test form Revised 10/01/78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones oniv).