

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **077754**
Unit **as des. designated Org. Unit.**

SUNDRY NOTICES AND REPORTS ON WELLS

| | | | |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL..... | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF WATER SHUT-OFF..... | |
| NOTICE OF INTENTION TO CHANGE PLANS..... | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | | SUBSEQUENT REPORT OF ALTERING CASING..... | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | | SUBSEQUENT REPORT OF REDRILLING OR REPAIR..... | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | | SUBSEQUENT REPORT OF ABANDONMENT..... | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | | SUPPLEMENTARY WELL HISTORY..... | |
| NOTICE OF INTENTION TO ABANDON WELL..... | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

February 15, 1951
Sullivan-Hill No. 1 - Kelly
Well No. 1 is located 990 ft. from ~~XXX~~ [S] line and 990 ft. from ~~XXX~~ [W] line of sec. 3
NE SW SW Cor 3 30N 10W
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~surface~~ ^{Ground} above sea level is 6333 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

The above well will be drilled to and completed in the Mesa Verde formation. Rotary tools will be used to drill to and set pipe on the Cliff house or Point Lookout sand whichever shall be judged the most likely for production. Cable tools shall be used to drill the remainder of the hole to the top of the Mancos shale. If after drilling to the Mancos the Mesa Verde shall be considered productive it will be shot and cleaned out. Size of this shot shall be determined later. The following casing program will be used: 10 3/4 cemented to approximately 150 feet and 7 inch cemented to the top of either the Cliff House or the Point Lookout.

Circulate cement behind surface pipe.

Isolate Cliff House from upper formation by covering with cement.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Jack Sullivan, operator

Address 341 No. Foothill Road

Beverly Hills, Calif.

By *Carl Sullivan*

Title