## Revised 12-1-55

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

nitial XX			_							
Initial Annual Annual				Spec	<del></del>	Date of Test <b>3/14/60</b>		3/14/60		
ompany Astec	011 & Gen	Company	I	Lease	<u>Xye</u>		Wel	1 No	6	
nit L	Sec. 12	Twp3	Rge	e. 11W	Purc	haser	Courthern (	kalon Or	thering Syst	
asing 2 7/8	Wt. <b>6.40</b>	I.D	عاملاً. Set	t at 249	<b>9</b> Pe:	rf <b>2</b>	436	То	2467	
ubing <b>b</b>										
as Pay: From										
roducing Thru								•		
ate of Comple					Sin	രി പെയരാർ ദ	anhoad C	$c \sim c$	.O. Dual	
ase or compre	01011		Facker			neserve	oll lemb.			
	A desirable distance of the same of the sa	• ( )		OBSERVE	SD DATA					
ested Through	ested Through (Choke) (Me							Type Taps		
(Prover)	Flow (Choke	w Data )   Press	Diff.	Temp.	Tubing Press.	Data Temp.	Casing D	ata Temp.	Duratio	
o. (Line) Size		e)		o <sub>F</sub> .	psig		psig	°F•	of Flor Hr.	
ī	<del></del>	PSIS	, 11W	1.	harg		<b>569</b>	1. •	8 days	
d	0.790						1.10	50	3 bre.	
•										
			F	LOW CALC	CULATIONS	S				
Coeffic	$(24-Hour)$ $\sqrt{h_W}$				Flow Temp. Grav		ity Compress. tor Factor		Rate of Flow	
			psia	Ft	5	Fg	Fpv		@ 15.025 psia	
. 12.35%			1/25	1,00	9	0.9608	1.08		2205	
c										
. 1	į.									
0										
•			PRE	ESSURE CA	LLCUIATIO	ONS				
s Liquid Hydr				cf/bbl.	LCU:ATI	Speci	ific Gravi			
s Liquid Hydroavity of Liqu	id Hydroca	arbons	<del></del>		ALCU!ATI(	Speci Speci		ty Flow	rator Gas ing Fluid	
s Liquid Hydro avity of Liqu	id Hydroca	arbons	<del></del>	cf/bbl.	ALCU:ATI(	Speci Speci	ific Gravi	ty Flow	ing Fluid	
s Liquid Hydro avity of Liqu	id Hydroca	arbons (1-e <sup>-s</sup> )		cf/bbl. deg.		Speci Speci P <sub>c</sub>	fic Gravi	ty Flow PC	ing Fluid	
P <sub>w</sub> Pt (psia)	id Hydroca	rbons (1-e <sup>-s</sup> )	(F <sub>c</sub> Q) <sup>2</sup>	cf/bbl. deg.  (Fc	Q) <sup>2</sup> -e-s)	Speci Speci Pc P <sub>w</sub> 2	p <sub>c</sub> -p <sub>w</sub> <sup>2</sup>	ty Flow PC	ing Fluid	
s Liquid Hydroavity of Liqu	id Hydroca	arbons (1-e <sup>-s</sup> )	(F <sub>c</sub> Q) <sup>2</sup>	cf/bbl. deg. (Fc	Q) <sup>2</sup> -e-s)	Speci Speci P <sub>c</sub>	fic Gravi	ty Flow PC	ing Fluid	
s Liquid Hydroavity of Liqu	id Hydroca	rbons (1-e <sup>-s</sup> )	(F <sub>c</sub> Q) <sup>2</sup>	cf/bbl. deg.  (Fc	Q) <sup>2</sup> -e-s)	Speci Speci Pc P <sub>w</sub> 2	p <sub>c</sub> -p <sub>w</sub> <sup>2</sup>	ty Flow PC	ing Fluid	
P <sub>W</sub> Pt (psia)	id Hydroca	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	cf/bbl(Fc	Q) <sup>2</sup> e-s)	Speci Speci P <sub>C</sub> P <sub>w</sub> 2	p <sub>c</sub> -p <sub>w</sub> <sup>2</sup>	ty Flow PC	ing Fluid	
P <sub>W</sub> Pt (psia) bsolute Potent	Pt 33.124	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	cf/bbl.deg.  (Fc (1-	Q) <sup>2</sup> e-s)	Speci Speci Pc P <sub>w</sub> 2	p <sub>c</sub> -p <sub>w</sub> <sup>2</sup>	ty Flow PC	ing Fluid	
P <sub>W</sub> Pt (psia)  bsolute Potent	Pt 33.124	F <sub>c</sub> Q  12.340  3164  Gra Comp	(F <sub>c</sub> Q) <sup>2</sup>	cf/bbl.deg.  (Fc (1-	Q) <sup>2</sup> -e-s)	Speci Speci Pc P <sub>w</sub> 2	p <sub>c</sub> -p <sub>w</sub> <sup>2</sup>	ty Flow P2 Ca	ing Fluid  Pw Pc	

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- $P_c$  72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_f$  Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- $F_t$  Flowing temperature correction factor.
- $F_{py}$  Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_W$  cannot be taken because of manner of completion or condition of well, then  $P_W$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{t}$ .

STATE OF NEW MEXICO	
CONSERVATION COM	i
D.S. CERGO	3
NUMBER OF COPIES RECEIVED	
0 57 1 7	7
\$. H.A FE	
U.S. 5.5	
3 0 000	
TRAKS, ORTER JOH	
G.E.	-
TALC FICE	1
	4
The state of the s	<u>.</u> !