


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 27 07802  
Unit 1/2 Sec. 10



SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED  
JUN 26 1957  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 25, 1957

Well No. Fluorine is located 1700 ft. from S line and 990 ft. from W line of sec. 10

SW 1/4 Sec. 10 (1/4 Sec. and Sec. No.) 3N (Twp.) 9E (Range) 107N (Meridian)  
Fluorine (Field) Santa Fe (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 4277 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set bridge plug in 7" casing at 5030. Perforated 7" w/ 2 bullets at 4930. Squashed C.I. section w/ 200 cu. cement. Max. pressure 3000#. Located hole in 7" casing approx. 1850'. Squashed w/ 150 cu. cement, drilled retainer. Pipe test indicated hole still open approx. 1850', re-squashed w/ 275 cu. cement. Max. pressure 3000#, drilled cement & GO to 5450, tested pipe 2000# for 1 hour. Drilled plug at 5450 and GO to 5650'. Free open hole 5219 to 5450 w/ 41.5 lb gals water 13,000# sand, pressures 500 - 2000# in 50 NW. Set plug 1950 perforated 7" casing 1850 - 1950 w/ 2 1/2 bullets. Flow w/ 64,250 gals water and 10,000# sand pressures 900 - 750, in 50 NW. GO 1950. On gauge 1850 NW, drilled plug, GO to 5400. P.L. increased flow 1110 NW. Total 5450 NW. 2" line tubing landed at 5251'. Well 21 NO re-connection to P.L.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Bulhi-Taylor Oil Corporation  
Address P. O. Box 1175  
Farmington, New Mexico  
By D. McNeill  
Title Dist. Supt.

100

[illegible]