Form 9-331
(May 1963)

# UNITED STATES
# DEPARTMENT OF THE INTERIOR
## GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR
**AMOCO PRODUCTION COMPANY**

3. ADDRESS OF OPERATOR
**501 Airport Drive, Farmington, New Mexico 87401**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
**1650' FSL & 1455' FEL**

5. LEASE DESIGNATION AND SERIAL NO.
**078139**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
**E. E. Elliott "C"**

9. WELL NO.
**1**

10. FIELD AND POOL, OR WILDCAT
**Undesignated Fruitland-Blanco Pictured Cliffs**

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
**SE/4 Section 9, T-30-N, R-9-W**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
**GL 6085', KB 6098'**

12. COUNTY OR PARISH
**San Juan**

13. STATE
**New Mexico**

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

| NOTICE OF INTENTION TO: | | | | SUBSEQUENT REPORT OF: | | | |
|---|---|---|---|---|---|---|---|
| TEST WATER SHUT-OFF | ☐ | PULL OR ALTER CASING | ☐ | WATER SHUT-OFF | ☐ | REPAIRING WELL | ☐ |
| FRACTURE TREAT | ☐ | MULTIPLE COMPLETE | ☐ | FRACTURE TREATMENT | ☒ | ALTERING CASING | ☐ |
| SHOOT OR ACIDIZE | ☐ | ABANDON* | ☐ | SHOOTING OR ACIDIZING | ☐ | ABANDONMENT* | ☐ |
| REPAIR WELL | ☐ | CHANGE PLANS | ☐ | **Perforate** | | | ☒ |
| (Other) | ☐ | | ☐ | NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) | | | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

**Set a Model "P" cast iron bridge plug at 2796'. Spotted 500 gallons 15% HCl. Tested casing with 2000 psi OK. Perforated 2608-18', 2635-43' with 1 shot per foot. Sand-water fracad down casing with 20,000 gallons water treated with 0.8% KCl and 7 pounds Gel per 1000 gallons and 20,000 pounds 20-40 sand. Breakdown pressure 1800 psi, treating pressures 2000-2000-1800. Average injection rate 25 BPM.**

RECEIVED
JAN 12 1972
OIL CON. COM.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE **Area Engineer** DATE **January 10, 1972**

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

## Instructions

**General:** This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963 O-685229

847 - 485