

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Formation County Initial Annual Special Date of Test Company Lease Well No. Unit K Sec. 9 Twp. 30 Rge. 12 Purchaser Casing Wt. I.D. Set at Perf. To Tubing Wt. I.D. Set at Perf. To Gas Pay: From To L xG -GL Bar.Press. Producing Thru: Casing Tubing Type Well

Single-Bradenhead-G. G. or G.O. Dual

Date of Completion: Packer Reservoir Temp.

OBSERVED DATA

Tested Through (Prover) (Choke) (Meter) Type Taps

Flow Data						Tubing Data		Casing Data		Duration of Flow Hr.
No.	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h_w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						1355		1356		7 Days
1.		3/4				120	76	534		3 Hours
2.										
3.										
4.										
5.										


FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w P_f}$	Pressure psia	Flow Temp. Factor F_t	Gravity Factor F_g	Compress. Factor F_{pv}	Rate of Flow Q -MCFPD @ 15.025 psia
1.	12.3650		132	0.850	0.968	1.011	1.338
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio cf/bbl.Gravity of Liquid Hydrocarbons deg. F_c ($1-e^{-s}$) Specific Gravity Separator Gas Specific Gravity Flowing Fluid P_c 1368 P_c^2 3873.024

No.	P_w P_t (psia)	P_t^2	$F_c Q$	$(F_c Q)^2$	$(F_c Q)^2$ ($1-e^{-s}$)	P_w^2	$P_c^2 - P_w^2$	Cal. P_w	$\frac{P_w}{P_c}$
1.	546					298116	3574.08		
2.									
3.									
4.									
5.									

Absolute Potential: 1654 MCFPD; n 0.75 (1.0615)COMPANY ADDRESS AGENT and TITLE WITNESSED COMPANY REMARKS 

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia

P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressibility factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .