UNITED STATES DEPARTMENT OF THE INTERIOR SECUCION CURVEY

0.0/ 001000	
S.₹. 081226	

б.	HF INDIAN,	ALLOTTEE	OR	TRIBE	MAME

GEOLUGICAL SURVEY	o. If the bridge the control of the
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME Horseshoe Gallup Unit
Do not use this form for proposals to drill or to deepen or blug back to a different reservoir luse Form 9-831-0 for such proposals.)	8. FARM OR LEASE NAME Horseshoe Gallup Unit
1. on — gas — other Infection	9. WELL NO.
2. NAME OF OPERATOR ARCO Oil and Gas Co., a	275
Division of Atlantic Richfield Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 707 - 17th Street,	Horseshoe Gallup
P.O. Box 5540, Denver, Colo. 80217	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF MELL REPORT LOCATION CLEARLY. See space 17 below.) Unit J,	AREA Sec. 9-30N-16W
AT SURFACE: 1450' FSL & 1980' FEL, Sec. 9	12. COUNTY OR PARISH! 13. STATE
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	None Assigned
REPORT, OR CTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF TO	1200
TEST WATER SHUT-OFF 🔲 🔲	
FRACTURE TREAT	1034 I III
SHOOT OR ACIDIZE	BECEIVED
REPAIR WELL	(NOTE) Report relates or multiple completion or zone
PULL OR ALTER CASING	- COT 6: 1981
MULTIPLE COMPLETE	JAN O
ABANDON*	SURVEY
(other)	U. S. GEOLOGICAL SURVEY

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This notice supercedes our Sundry Notices dated August 31, 1982 on the subject well.

ARCO now proposes to plug and abandon this well, as per the attached revised P & A Procedure.

(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982 , both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division(copies attached to our August 31, 1982 Sundry Notice).

	4 1 1 1 1 1 1	To the second		
Subsurface Safety Valve: Manu. and Type	JAM 1 3 1083		Set @	Ft.
18. I hereby certify that the foregoing is true a SIGNED SEE HOSE	nd confedil CON. DIV.	-DATE	December 1,	30 1982_
	s space for Federal or State office use)			
APPROVED BY CONDITIONS OF APPROVAL IF AND		_ DATE _		<u>.</u>
For The Kellen	MMOCO			
I all the second	*See Instructions on Reverse Side			

HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REVISED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30' cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.

NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 - 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.

TABLE I

Horashoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

List of Wells

	₹	 	2 _	
	No.	-29	<u>خ</u>	
3.	No.	103	R	
4.	No.	105	A	
5.	No.	113	A	
) 6.	<u> </u>	306		
), 0.	110.			
7.	No.	130	C	
8.	No.	132	C	
9.	No.	135	C	
10.	No.	137	C	
11.	No.	139	C	
12.	No.	141	C	
13.	No.	143	D	
14.	No.	145	D	
15.	No.	148	D	
16.	No.	150	D	
17.	No.	152	D	
18.	No.	154	D	
19.	No.	156	D	
-00_		-160		

21.	Nc.	215	D.
	- No	162	-0-
23.	No.	164	D
-24.	No.	-169 -	-) -
25.	No.	171	D
26.	No.	173	D
27.	No.	175	D
- 22	No.	160-	
29.	No.	182	Ø
30.	No.	184	D
31.	No.	186	٥
-32.	No.	192	0
33.	No.	194	D.
34.	No.	196	D
35.	No.	201	9
36.	No.	203	D
37.	No.	205	D
38.	No.	207	D
39.	No.	213	Q
40.	No.	217	D

<u> </u>	•	No.	223	D.
42		No.	225	C
(3m/t2) 43		No.	227	D
44		No.	229	D
45		No.	238	D
(State) 46	· .	No.	240	D
47		No.	248	D
48	·	No.	250	\Box
49		No.	259	D
50		No.	261	C
51	••	No.	263	C
52	2.	No.	269	C
53	3.	No.	274	C
54	١.	No.	275	C
55	5.	No.	73	Ą
-36	.	No.	199	0
-51	<u>.</u>	No:	211	-D -
				_