Form 3160-5 (November 198 (Formerly 9-3		Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 LEASE DESIGNATION AND SERIAL NO NM 077282
(Do not	SUNDRY NOTICES AND REPORTS ON WELLS use this form for proposals to drill or to deepen or plug back to a different rese Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1.		7. UNIT AGREEMENT NAME
OIL X GAS WELL OTHER		Northeast Hogback
2. NAME OF OPERATOR		8. FARM OR LEASE NAME
BHP Petro		
3. ADDRESS OF OPERATOR		9. WBLL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State regularies)		32
5613 DTC Parkway, Ste. 600, Englewood, CO 80111 LOCATION OF WELL (Report location clearly and in accordance with any State requirements EVED At surface		VFD 10. FIELD AND POOL, OR WILDCAT
	n_{0x}	Horseshoe Gallup 11. SEC., T., B., M., OR BLE, AND
226	00720	1986 SURVEY OR AREA
	BUREAU OF	Sec. 11, T30N, R16W
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, CM, NGTON DE	NAGEARD 12. COUNTY OR PARISH 13. STATE
	15. ELEVATIONS (Show whether DF, RT, UNIVESTON RESOL	Sec. 11, T30N, R16W 12. COUNTY OF PARISH 13. STATE INCE AREA New Mexico
16.	Check Appropriate Box To Indicate Nature of Notice, R	and a Other Date
	NOTICE OF INTENTION TO:	
		SUBSEQUENT REPORT OF:
TEST WATE	Walsa Shul-OF	F REPAIRING WELL
FRACTURE T		
SHOOT OR A	Shooting on Ac	IDIZING ABANDONMENT* X
(Other)	(Other)	port results of multiple completion on Well
17. DESCRIBE PRO	Ompletion Completion Complet	or Recompletion Report and Log form.)
proposed nent to thi		true vertical depths for all markers and zones perti-
The subje	ect well was plugged as follows:	
9/30/86:	Perf'd @ 270'. Rigged Up, NU BOP. TIH w/tbg. Stung into packer @ 1795'. Mixed and pumped 30 sx Class "B" w/3% CaCl ₂ . Put 10 sx below packer and 20 sx above packer (TOC 1530'). PU to 1530'. Closed casing valve and opened bradenhead valve. Circulated well w/9.2#/gal mud. Closed Bradenhead valve and opened casing valve. Finished circulating well w/mud. PU to 270'. Opened Bradenhead valve. Mixed and pumped 30 sx Class "B" w/3% CaCl ₂ . Set plug from 270' to 160' inside and outside casing. PU to 50'. SDFN.	
10/1/86:	Set cement plug from 50' to surface. Cut off we Cleaned up location.	ellhead. Installed dry hole marker
	Location will be restored and reseeded as requir	red when in season.
	Approximition to provide a state with of Liebility was a second of the with of surface received as a second of the with of surface received.	970 7198p D

Liebility or surface resting that the foregoing is true and correct

SIGNED Paul Bertoglio TITLE Production Superintendent

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCO

NMOCO
Title 18 U.S.C. Section 1901, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any faise, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.