NUMBER OF COPIE	S FECEIV	ED	
DIS	TRIBUTIO	N	 _
SANTA FE			
FILE			
U.S.G.S.			
LAND OFFICE			_
TRANSPORTER	OIL		
	GAS		_
PRORATION OFFE	CE		_

NEW MEXICO OIL CONSERVATION COMMISSION FORM C+103

U.S.G.S.								
LAND OFFICE OIL TRANSPORTER GAS		M	ISCELLAN	EOUS	REPOR	TS ON	WELLS	
PRORATION OFFICE		(Submit to	o appropriate D	istrict	Office as p	er Comm	nission Rule 1106))
lame of Company	EXACO I	Inc.			x 810,		ington, New	
L. M. Ba			1 1	F	Section Tov	30	North Rang	2 West
oat August of 19	61 F	a Basin(Da	nated (Men	BBL VE	Coun	ity	San Juan	
			REPORT OF: (
Beginning Drilling	Operations		g Test and Ceme	ent Job		Other (Ex	cplain):	
Plugging Detailed account of work			lial Work					
and full cir the hole was from Mr. E. casing progr in 2 stages through bott 123# of gils	rill pirculating conditions on the condition of the condi	lpe was stri lon was regal ltioned to mold of the this well. two stage to casing with	ipped into ined. The casing oil Consequent 4790' or col set and 500 sactores.	o the he log. Vervail of 7" t 227 ks of	e hole a ogging d Verbal a tion Con casing 73'. Co 50/50 owed by	and t tool appro mmiss g was ement pozm 100 stage	he well was was recover val was rec ion to chan cemented s ed first st ix with 4% sacks of 50	killed red and seived age the at 4800' cage gel and 0/50 pozmix
of 50/50 pos of cement to tool at 2273 Drilled out	emix with R' with	th 4% gel. t 280'. Ten n 1000# pres t plug in bo	Ran tem sted casis ssure for ottom of Position Drilling	perating be 30 mg 7° co	ture surefore as ainutes asing as Compan	rvey nd af . Ca nd cl	which indicater drilling tested eaned out hexaco Inc.	sated top ng out DV l OK.
of 50/50 por of cement to tool at 2273 Drilled out	emix with the cement	ith 4% gel. t 280'. Ten n 1000# pres t plug in bo	Ran tem sted casis ssure for ottom of Position Drilling	peraing be 30 mg be 7 mg be 7 mg be 7 mg be 7 mg be 10 mg	efore and sinutes asing and companal co	rvey nd af . Ca nd cl	which indicater drilling tested eaned out hexaco Inc.	sated toping out DV i OK.
of 50/50 por of cement to tool at 2273 Drilled out	emix with the cement	th 4% gel. t 280'. Ten n 1000# pres t plug in bo	Ran temsted cash seure for ottom of Position Drilling	peraing be 30 mg be 7 mg be 7 mg be 7 mg be 7 mg be 10 mg	efore and einutes asing and eman Companan Compan	rvey nd af . Ca nd cl	which indicater drilling sing tested eaned out hexaco Inc.	sated top ng out DV 1 OK.
of 50/50 por of cement to tool at 2273 Drilled out	be at be at cement. Hogo	th 4% gel. t 280'. Ten n 1000# pres t plug in bo	Ran tem sted casis ssure for ottom of Position Drilling W FOR REMED ORIGINAL N	perating be 30 mg be 7 cm	efore and einutes asing and eman Companan Compan	rvey nd af . Ca nd cl pany T	which indicater drilling tested eaned out hexaco Inc.	ated toping out DV l OK. lole (over)
of 50/50 por of cement to tool at 2273 Drilled out Witnessed by C. (mix with the common to the com	th 4% gel. t 280'. Ten t 1000# pres t plug in bo	Ran tem sted casis ssure for ottom of Position Drilling W FOR REMED ORIGINAL N	perating be 30 mg be 7 cm	efore and end of the companies of the co	rvey nd af . Ca nd cl pany T	which indicater drilling tested eaned out hexaco Inc.	ated toping out DV l OK. lole (over)
of 50/50 pos of cement to tool at 2273 Drilled out	mix with the common to the com	th 4% gel. t 280'. Ten t 1000# pres t plug in bo	Ran tem sted casis saure for ottom of Position Drilling W FOR REMELE ORIGINAL TO PBTD	Fore Olal W. WELL D. Oil Strin	efore and sinutes asing an Compan ORK REPO ATA Proposition of the prop	rvey nd af . Ca nd cl pany Torts on	which indicater drilling tested eaned out hexaco Inc.	ated toping out DV l OK. lole (over)
of 50/50 por of cement to tool at 2273 Drilled out Vitnessed by C. (Description of the content of the cement to	mix with the common to the com	th 4% gel. t 280'. Ten t 1000# pres t plug in bo	Ran tem sted casis saure for ottom of Position Drilling W FOR REMED ORIGINAL W PBTD RESULTS OF	Fore Oil Strin	efore an ainutes asing as Compan Cover Cove	rvey nd af . Ca nd cl pany Toroducing	which indicater drilling tested eaned out hexaco Inc. LY	ated toping out DV i OK. Nole (over)
of 50/50 por of cement to tool at 2273 Drilled out Witnessed by C. (DF Elev. Tubing Diameter Perforated Interval Open Hole Interval	mix with the second of the sec	th 4% gel. t 280'. Ten t 1000# pres t plug in bo	Ran tem sted casis saure for ottom of Position Drilling W FOR REMELE ORIGINAL TO PBTD	Producing WORK	efore and sinutes asing an Compan ORK REPO ATA Proposition of the prop	rvey nd af . Ca nd cl pany T ORTS OA roducing	which indicater drilling tested eaned out hexaco Inc.	cated toping out DV i OK. Nole (over)
of 50/50 por of cement to tool at 227; Drilled out Witnessed by C. (DF Elev. Tubing Diameter Perforated Interval Open Hole Interval Date	mix with the second of the sec	th 4% gel. t 280'. Test t 1000# pres t plug in bo FILL IN BELOV Tubing Depth Oil Production	Ran tem sted casis saure for ottom of Position Drilling W FOR REMED ORIGINAL S PBTD RESULTS OF Gas Produc	Producing WORK	efore an ainutes asing a compan Compan Compan Compan Compan Compan Compan Compan Compan Cover Co	rvey nd af . Ca nd cl pany T ORTS OA roducing	which indicater drilling tested eaned out he kxACO Inc. Carry Car	gated toping out DV l OK. lole (over) completion Date pth Gas Well Potential
of 50/50 por of cement to tool at 227; Drilled out Witnessed by C. (D. F. Elev. Tubing Diameter Perforated Interval Open Hole Interval Test Date Test Test Test Test Test Test Test Te	mix with the second of the sec	th 4% gel. t 280'. Test t 1000# pres t plug in bo FILL IN BELOV Tubing Depth Oil Production	Ran tem sted casis saure for ottom of Position Drilling W FOR REMED ORIGINAL S PBTD RESULTS OF Gas Produc	Fore Oil Strin	efore an ainutes asing an Compan Compan Compan ORK REPO ATA Proposition of Companies of Compani	rvey nd af . Ca nd cl pany T ORTS OA roducing	which indicater drilling tested eaned out he will be to be to be the standard of the standard	description Date Gas Well Potential MCFPD
of 50/50 por of cement to tool at 2273 Drilled out Witnessed by C. (D. F. Elev. Tubing Diameter Perforated Interval Open Hole Interval Test Before Workover After Workover	mix with the second of the sec	th 4% gel. t 280'. Test t 1000# pres t plug in bo FILL IN BELOV Tubing Depth Oil Production	Ran tem sted casis saure for ottom of Position Drilling W FOR REMED ORIGINAL S PBTD RESULTS OF Gas Produc	Fore Old Well D	efore an ainutes asing an Compan Compan Compan ORK REPO ATA Proposition of Companies of Compani	rvey nd af . Ca nd cl pany T ORTS ON roducing	which indicater drilling tested eaned out he will be seened out he	gated toping out DV l OK. lole (over) completion Date pth Gas Well Potential

to 6764. Hung 2079' of 4-1/2" liner in 7" casing with Bassh-Ross Liner Hanger. Liner hanger was set at 4672' with bottom of liner at 6764'. Cemented liner with 400 sacks of 50/50 posmix with 2% gel. Set test tool at 4621 and tested liner with 3500# pressure for 12 minutes. Liner 4621' and tested liner with 3500# pressure for 12 minutes. Liner tested 0K. Fulled test tool and set lead seal in liner hanger.

STATE OF NEW	EXICO		}
OIL ATION		ON	
MUMBER OF COP ES RECEIVE	-	3	
SANTA FE			
U.S.G.S.			
TRANSPORTER OIL GAS	_		
PRORATION OFFICE OPERATOR	 		