S.F. 081226-C

UNITED STATES							
DEPARTMENT	OF	THE	INTERIOR				
GEOLOGICAL SURVEY							

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME USA					
SUNDRY NOTICES AND REPORTS ON WELLS The notices this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME Horseshoe Gallup Unit					
reservoir, use Form 9-231-0 for such proposals.)	8. FARM OR LEASE NAME Horseshoe Gallup Unit					
1. of gas other	9. WELL NO. 269					
Tivision of Atlantic Richfield Company  3. ADDRESS OF CRERATOR 707 - 17th Street, P.O. Box 5540, Denver, Colo. 30217	10. FIELD OR WILDCAT NAME Horseshoe Gallup  11. SEC., T., R., M., OR BLK, AND SURVEY OR					
4. LOCATION OF WELL REPORT LOCATION CLEARLY. See space 17 below.) Unit H, AT SURFACE: 1746' FNL & 1122' FEL, Sec. 9 AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Sec. 9-30N-16W  12. COUNTY OR PARISH 13. STATE  San Juan New Mexico					
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR CTHER DATA	14. API NO.  None Assigned  15 ELEVATIONS (SHOW DF, KDB, AND WD)					
REQUEST FOR APPROVAL TO:  TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*  (other)	Report Report C FIN Fredon or kone change on form \$300 Fredon or kone					
(Outlet)	U. S. GEOLOGICAL SURVEY					

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* P11-1-82

This notice supercedes our Sundry Notice Sdated August 31, 1982 on the subject well.

ARCO now proposes to plug and abandon this well, as per the attached <u>revised P & A Procedure.</u>


(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982 , both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division (copies attached our August 31, 1982 Sundry Notice).

	. 7.5	rk t (58 <b>3</b>		
Subsurface Safety Valve: Manu. and	Туре		Set @	Ft.
18. I hereby certify that the foregoing SIGNED S. ROSE ROSE	ng is true and correct	<del>- 1</del>	December 2	්ට 1982
SIGNED S. C. ROSE	TITLE DIST.Pro	OG. SUPT DATE	Wovemmer I,	1302
A	(This space for Federal or St.	ate office use)		
APPROVED BY	TITLE	DATE		
CONDITIONS OF APPROVAL IF ANY:	**************************************	waren Sida		
1	*See Instructions on Rev	verse 21de		

## HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REVISED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30' cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.

NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 - 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.



## TABLE I

Horashoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

## List of Wells

	Nc. ≎6 -{	<del>}</del>	21.	No.	215	٥		41.	No.	223
	No. 29		-22.	<del>- No -</del>	162	0		42.	No.	225
3.	No. 103	А	23.	No.	164	D		(State) 43.	No.	227
4.	No. 105	Д	-24	No.	169	<del>-)-</del>	•	44.	No.	229
5.	No. 113	А	25.	No.	171	D		45.	No.	238
<del>&gt; 5.</del>	No. 126		26.	No.	173	D	į.	(State) 46.	No.	240
7.	No. 130	C	27.	No.	175	D		47.	No.	248
з.	No. 132	<i>C</i> , , , , , , , , , , , , , , , , , , ,	-38	NO.	130	<del>-</del>	•	48.	No.	250
9.	No. 135	C	29.	No.	182	D		49.	No.	259
10.	No. 137	C	30.	No.	184	D		50.	No.	261
11.	No. 139	Ç	31.	No.	186	۵		51.	No.	263
12.	No. 141	C	-32	No.	192	0		52.	No.	269
13.	No. 143	D	33.	No.	194	D.		53.	No.	274
14.	No. 145	D	34.	No.	196	D		54.	No.	275
15.	No. 148	D	35.	- No-	<del>-201</del>	-9		55.	No.	73
16.	No. 150	D	36.	No.	203	D		<del>-56.</del>	No.	-199
17.	No. 152	D	37.	No.	205	D		<del>-57.</del>	No.	-211
18.	No. 154	D	38.	No.	207	D				
19.	No. 156	D	39.	No.	213	Q		in the second	, m	

40. No. 217 D

Che (Comply

D

D

D

0