
Form 9-331 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa Fe
Lease No	24-024158
Unit	

SUNDRY NOTICES AND REPORTS ON WELLS

						
NOTICE OF INT	ENTION TO DRILL		SUBSEQUENT REPO	RT OF WATER SHUT	-OFF	1
	ENTION TO CHANGE PLANS		SUBSEQUENT REPO	RT OF SHOOTING OF	R ACIDIZING	
	ENTION TO TEST WATER SHUT-	1 11		RT OF ALTERING CA		
NOTICE OF INT	ENTION TO RE-DRILL OR REPAI	R WELL		RT OF RE-DRILLING		
IOTICE OF INT	ENTION TO SHOOT OR ACIDIZE			RT OF ABANDONMEN		
OTICE OF INT	ENTION TO PULL OR ALTER CAS	SING.	SUPPLEMENTARY W			
IOTICE OF INT	ENTION TO ABANDON WELL				1 2	
						
	(INDICATE ABOVE	BY CHECK MARK NATU	RE OF REPORT, NOT	ICE, OR OTHER DATA		
Bla ell No. 11-	nco 30-12 9 is located 18	1N			11 2 11 :	, 19 •
ATTO: ILL.	is located	T. It. Hom.	ine and	ft. from	\overline{W} line of sec.	
(⅓ Šec. a	nd Sec. No.) ("	Twp.) (Range		(Meridian)		
ildest (Pictured Cliffs)	Sen Auen	,	(Mendian)	Marrian	
	ield)	(County or Subd	livision)	(State	or Territory)	
		points, and an other tr	ghts, and lengths o	work)		
udded 9- H-40 24 reg w/3	7/8" hole at 7:40 f 8-30 casing w/5: I CaCl. POB 12:0	sands; show sizes, weipoints, and all other in	ghts, and lengths on portant proposed Drid to 13	io' and set	111.75* of	7-5/8
udded 9- 3-40 24	7/8" hole at 7:40 f 8-30 casing w/5: I CaCl. POB 12:0	sands; show sizes, weipoints, and all other in	ghts, and lengths on portant proposed Drid to 13	io' and set	111.75* of	7-5/8
udded 9- H-40 24 reg w/3 lg sheed	7/8" hole at 7:40 f 8-30 casing w/B. I CaCl. POB 12:0)	sands; show sizes, weipoints, and all other in paids 3-16-57. Sher guide shi an 3-17-57.	ghts, and lengths on a price of the last o	iO' and set. '. Cemente hours WOC,	111.75' of d to surface casing test	7-5/8
understand ti	7/8" hole at 7:40 f 8-MD casing w/B I CaCl. POB 12:0	sands; show sizes, weipoints, and all other in paids 3-16-57. Sher guide shi an 3-17-57.	ghts, and lengths on a price of the last o	iO' and set. '. Cemente hours WOC,	111.75' of d to surface casing test	7-5/8
udded 9- H-40 24 reg w/3 lg sheed	7/8" hole at 7:40 f 8-30 casing w/B. I CaCl. POB 12:0)	sands; show sizes, weipoints, and all other in points, and all other in part 3-16-57. sker guide shit an 3-17-57.	ghts, and lengths on a price of the last o	Survey before opera	111.75' of d to surface casing test	7-5/8
understand the	7/8" hole at 7:40 f 8-20 casing w/B. I CaCl. POB 12:0)	sands; show sizes, weipoints, and all other in points, and all other in part 3-16-57. sker guide shall as 3-17-57.	ghts, and lengths on a price of the last o	iO' and set. '. Cemente hours WOC,	111.75 of d to surface casing test	7-5/8