Form (Feb.		8
	7	

X

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	Sante	Fe
Lease No.	M+-05#1	58
Unit		

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLA	NS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER	SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OF	REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPORT
IOTICE OF INTENTION TO SHOOT OR A	CIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
IOTICE OF INTENTION TO PULL OR ALI		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WE	FLL	JAN 4952
(IND)CATE	ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER DATA)
		Jamuary 16 19 62
R.E. McKenzie Gas Un	it "A"	
ll No. 1 is located	1 910 _ ft. from	1. $\left\{\begin{matrix} \mathbf{N} \\ \mathbf{g} \end{matrix}\right\}$ line and
MR/4 Section 9	30N	124 MAPH FOLLIA
(1/ Sec. and Sec. No.)	(Twp.)	(Range) (Meridian)
doet dallus	Sen Amn	or Subdivision) (State or Territory)
(Piola)	level	
e elevation of the desired		vel is 5806 ft. JAN 1 9 1962
C CICYMEIOII OI CIIC CENTRE	above tou it.	1
		NON CONTRACTOR
	DETAI	ILS OF WORK
and committed surface	bjective sands; show size ing points, and all o	ILS OF WORK see, weights, and lengths of proposed casings; indicate mudding jobs, cement- other important proposed work)
and comented surface 8 joints (250') 8 5/ sacks Incor 25 BA-5. rs. Pressure tested	bjective sands; show sizing points, and all of casting as folds; (B, 24, J). Circulated casing to 600	ses, weights, and lengths of proposed casings; indicate midding jobs, cement- other important proposed work) 11.0ve: 1-55, SMES, casing and set at 263'. Cemented vi cement to surface. Pumped plug down and MCC 8 1 pounds for 30 min. Pressure held CK.
end commuted surface 8 joints (250') 8 5/ sacks Incor 25 BA-5. rs. Pressure tested	bjective sands; show sizing points, and all of casting as follows. Circulated casing to 500	ils of work ses, weights, and lengths of proposed casings; indicate mudding jobs, cement- other important proposed work) illows; -55, SHES, casing and set at 263'. Comented vi cement to surface. Pumped plug down and wor 8
and comented surface 8 joints (250°) 8 5/2 macks Incor 25 BA-5. The Pressure tested of the standard surface of the standard s	bjective sands; show sizing points, and all of casting as follows. Circulated casing to 500	ses, weights, and lengths of proposed casings; indicate midding jobs, cement- other important proposed work) 11.0ve: 1-55, SMES, casing and set at 263'. Cemented vi cement to surface. Pumped plug down and MCC 8 1 pounds for 30 min. Pressure held CK.