

X			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **SF**
Lease No. **081226-A**
Unit **Horseshoe Canyon**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 21, 1959

Well No. **1-A** is located **560** ft. from **N** line and **640** ft. from **W** line of sec. **9**
NW NW/4 Section 9 **30N** **16W** **NMPM**
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Horseshoe Gallup **San Juan** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **5305** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate cementing jobs, cementing points, and all other important proposed work)

6-20-69 Total Depth 1208'.

Ran 29 joints, 5-1/2", 15.50#, J-55 Casing (1200.39') set at 1207.39' with 25 sacks regular cement, 25 sacks Foxmix, 4% Gel., 1/4# Floccs per sack.

Held 1000#/30 Minutes.

Top of cement by temperature survey at 600'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Products Company**
Address **Post Office Box 1565**
Farmington, New Mexico
By **ORIGINAL SIGNED BY: WILLIAM A. BLAZENER**
Title **Petroleum Engineer**



RECEIVED JUL 1 1959